

Hazardous Chemical Substances Regulations

Contents:

Contents:.....	2
1. Definitions	4
2. Scope of application.....	6
3. Information and training	6
4. Duties of persons who may be exposed to hazardous chemical substances	7
5. Assessment of potential exposure	8
6. Air monitoring.....	9
7. Medical surveillance.....	10
8. Respirator zone.....	11
9. Records.....	11
10. Control of exposure to HCS	12
11. Personal protective equipment and facilities.....	13
12. Maintenance of control measures	15
13. Prohibitions	15
14. Labelling, packaging, transportation and storage	16
15. Disposal of hazardous chemical substances	16
16. Offences and Penalties	17
Annexure 1.....	17
Prevention and Control of Exposure	17
Medical Surveillance	18
4.2 BIOLOGICAL MONITORING OF EXPOSURE	18
4.2.2 Uses of biological monitoring	18
4.2.3 Important considerations in biological monitoring	19
4.2.4 Biological Exposure Indices (BEIs)	19
4.3 MEDICAL SCREENING.....	20
4.3.2 Types of examination	20
4.4 DESIGNING AND IMPLEMENTING A PROGRAMME OF MEDICAL SURVEILLANCE.....	20
Legal Background to Exposure Limits	22
Setting Occupational Exposure Limits	22
THE INDICATIVE CRITERIA.....	23
SETTING AN OEL-RL	24
SETTING AN OEL-CL	24
Applying Occupational Exposure Limits.....	24
GENERAL	25
UNITS OF MEASUREMENT	25
OCCUPATIONAL EXPOSURE LIMITS - CONTROL LIMITS; CL 9(TABLE 1).....	25
OCCUPATIONAL EXPOSURE LIMIT-RECOMMENDED LIMIT;OEL-RL (TABLE 2)	26
LONG-TERM AND SHORT-TERM EXPOSURE LIMITS	26
LIMITATIONS TO THE APPLICATION OF EXPOSURE LIMITS	27
EXPOSURE IN MINES	27
LEAD AND ASBESTOS.....	28
PESTICIDES.....	28
DUSTS.....	28
TOTAL INHALABLE DUST AND RESPIRABLE DUST	28
FUME.....	29

ABSORPTION THROUGH THE SKIN.....	29
SENSITISERS	29
OTHER FACTORS	30
Mixed Exposures	30
GENERAL.....	30
EFFECTS OF MIXED EXPOSURES	30
ASSESSMENT AND CONTROL	31
MONITORING MIXED EXPOSURE	32
COMPLICATING FACTORS	32
Biological Exposure Indices	33
Carcinogenic Compounds.....	41
Occupational Exposure Limits - Control Limits	46
Occupational Exposure Limits - Recommended Limits	48

1. Definitions

In this Schedule a word or expression to which a meaning has been assigned in the Act shall bear the meaning so assigned to it and unless the context otherwise indicates

“air monitoring”

means the monitoring of the concentrations of airborne hazardous chemical substances;

“Asbestos Regulations”

means the Asbestos Regulations published by Government Notice No. R. 773 of 10 April 1987 under section 43(5) of the Act;

“assessment”

means a programme to determine any risk from exposure to a hazardous chemical substance associated with any hazard thereof at the workplace in order to identify the steps needed to be taken to remove, reduce or control such hazard;

“BEi” or “biological exposure index”

is a reference value intended as a guideline for the evaluation of potential health hazards as listed in Table 3 of Annexure 1 hereby as revised from time to time and listed in the Government Gazette;

“engineering control measures”

means control measures that remove or reduce the exposure of persons at the workplace by means of engineering methods;

“exposed” means exposed to a hazardous chemical substance whilst at the workplace and “exposure” has a corresponding meaning;

“EH 42”

means the Guidance Note EH 42 of the Health and Safety Executive of the United Kingdom: Monitoring Strategies for Toxic Substances 1989 HSE ISBN 0 11885412 7 as revised from time to time and published in the Government Gazette;

“Facilities Regulations”

means the Facilities Regulations published by Government Notice No. It. 2362 of 5 October 1990 under section 43 (5) of the Act;

“General Administrative Regulations”

means the General Administrative Regulations published by Government Notice No. R. 2206 of 5 October 1984 under section 43 (5) of the Act;

“HCS” or “hazardous chemical substance”

means any toxic, harmful, corrosive, irritant or asphyxiate substance, or a mixture of such substances for which—

- (a) an occupational exposure limit is prescribed; or
- (b) an occupational exposure limit is not prescribed, but which creates a hazard to health;

“intake”

includes inhalation, ingestion or absorption through the skin or mucous membranes;

“Lead Regulations”

means the Lead Regulations published by Government Notice No. A. 586 of 22 March 1991 under section 43(5) of the Act;

“Measurement programme”

means a programme according to the monitoring strategy as contemplated in EH 42;

“Monitoring”

means the planning, carrying out and recording of the results of a measurement programme;

“OEL” or “occupational exposure limit”

means a limit value set by the Minister for stress factor in the workplace as revised from time to time by notice in the Government Gazette;

“OEL-CL” or “occupational exposure limit control limit”

means the occupational exposure limit for a hazardous chemical substance as listed in Table 1 of Annexure I hereby and ‘control limit’ has a corresponding meaning;

“OEL-RL” or “occupational exposure limit recommended limit”

means the occupational exposure limit for a hazardous chemical substance as listed in Table 2 of Annexure 1 hereby and ‘recommended limit’ has a corresponding meaning;

“OESSM”

means the Occupational Exposure Sampling Strategy Manual, published by the National Institute for Occupational Safety and Health (NIOSH), Publication No. 77-173 of 1977, United States of America: Department of Health, Education and Welfare;

“regional director”

means the regional director as defined in regulation 1 of the General Administrative Regulations

“respiratory protective equipment”

means a device which is worn over at least the mouth and nose to prevent the inhalation of airborne hazardous chemical substances and which is of a type, or conforms to a standard approved by the Minister;

“respirator zone”

means an area where the concentration of an airborne hazardous chemical substance exceeds the recommended limit for that substance;

“SABS 072”

the Code of Practice for the Safe Handling of Pesticides, SABS 072, published by the South African Bureau of Standards (SABS);

“SABS 0228”

the Code of Practice for the identification and Classification of Dangerous Substances and Goods, SABS 0228, published by the South African Bureau of Standards(SABS);

“SABS 0229”

the Code of Practice for Packaging of Dangerous Goods for Road and Rail Transportation in South Africa, SABS 0229, published by the South African Bureau of Standards(SABS);

2. Scope of application

1. Subject to the provisions of subregulation
2. Subject to the provisions of sub-regulation (2), these regulations shall apply to an employer or a self employed person who carries out work at a workplace which may expose any person to the intake of an HCS at the workplace.
3. The provisions of regulations 3(1), 6 and 7 shall not apply to:
 - a. a self employed person; or
 - b. a person who visits a workplace as contemplated in subregulation (1).
4. The provisions of these regulations shall not apply in the case where the Lead Regulations and Asbestos Regulations apply .

3. Information and training

1. An employer shall, before any employee is exposed or may be exposed, after consultation with the health and safety committee established for that section of the workplace, ensure that the employee is adequately and comprehensively informed and trained, as well as thereafter informed and trained at intervals as may be recommended by that health and safety committee, with regard to:
 - a. the contents and scope of these regulations;
 - b. the potential source exposure;
 - c. the potential risks to health caused by exposure;
 - d. the potential detrimental effect of exposure on his or her reproductive ability;
 - e. the measures to be taken by the employers to protect an employee against any risk from exposure;
 - f. the precautions to be taken by an employee to protect himself against the health risks associated with such exposure, including the wearing and use of protective clothing and respiratory protective equipment.

- g. the necessity, correct use, maintenance and potential of safety equipment, facilities and engineering control measures provided;
 - h. the necessity of personal air sampling and medical surveillance;
 - i. the importance of good housekeeping at the workplace and personal hygiene;
 - j. the safe working procedures regarding the use, handling, storage and labelling of the HCS at the workplace; and
 - k. procedures to be followed in the event of spillages, leakages or any similar emergency situation which could take place by accident.
2. An employer or self-employed person shall give written instructions of the procedures contemplated in paragraph (k) of subregulation (1) to the drivers of vehicles carrying the HCS.
3. An employer or a self employed person shall ensure that he himself or she herself or any other person who in any manner assists him or her in the carrying out or the conducting of his or her business, have the necessary information and has undergone sufficient training in order for him or her to identify the potential risks and precautions which should be taken.

4. Duties of persons who may be exposed to hazardous chemical substances

Every person who is or may be exposed, shall obey a lawful instruction given by or on behalf of the employer or a self employed person, regarding:

- a. the prevention of an HCS from being released;
- b. the wearing of personal protective equipment;
- c. the wearing of monitoring equipment to measure personal exposure;
- d. the reporting for health evaluations and biological tests as required by these regulations;
- e. the cleaning up and disposal of materials containing HCS;
- f. housekeeping at the workplace, personal hygiene and environmental and health practices; and
- g. information and training as contemplated in regulation 3.

5. Assessment of potential exposure

1. An employer or self employed person shall after consultation with the relevant health and safety representative or relevant health and safety committee, cause an immediate assessment to be made and thereafter at intervals not exceeding two years, to determine if any employee may be exposed by any route of intake.
2. The employer shall inform the relevant health and safety representative or relevant health and safety committee in writing of the arrangements made for the assessment contemplated in subregulation (1), give them reasonable time to comment thereon and ensure that the results of the assessment are made available to the relevant representatives or committees who may comment thereon.
3. When making the assessment, the employer or self employed person shall keep a record of the assessment and take into account such matters as:
 - a. the HCS to which an employee may be exposed;
 - b. what effects the HCS can have on an employee;
 - c. where the HCS may be present and in what physical form it is likely to be;
 - d. the route of intake by which and the extent to which an employee can be exposed; and
 - e. the nature of the work, process and any reasonable deterioration in, or failure of, any control measures.
4. If the assessment made in accordance with subregulation (3) indicates that any employee may be exposed, the employer shall ensure that monitoring is carried out in accordance with the provisions of regulations 6 and 7 and that the exposure shall be controlled as contemplated in regulation 10.
5. An employer shall review the assessment required by subregulation (1) forthwith if:
 - a. there is reason too suspect that the previous assessment is no longer valid; or
 - b. there has been a change in a process involving an HCS or in the methods, equipment or procedures in the use, handling, control or processing of the HCS,
 - c. and the provisions of subregulations (2) and (3) shall apply.

6. Air monitoring

1. Where the inhalation of an HCS is concerned, an employer contemplated in regulation 5(4) shall ensure that the measurement programme of the airborne concentrations of the HCS to which an employee is exposed, is:
 - a. carried out in accordance with the provisions of these regulations;
 - b. carried out only after the relevant health and safety representative or relevant health and safety committee has been informed thereof and given a reasonable opportunity to comment thereon;
 - c. carried out by an approved inspection authority or by a person whose ability to do the measurements is verified by an approved inspection authority;
 - d. representative of the exposure of employees to the airborne HCS in accordance with the provisions of subregulation (2); and
 - e. verified in accordance with the provisions of subregulation (3) if the measurements are carried out by a person who is not an approved inspection authority.
2. In order to comply with the provisions of subregulation (1).(d) an employer shall;
 - a. ensure that the measurement programme, in the case of a group measurement, makes provision for the selection of the number of persons for a sample to be done as contemplated in chapters 3 and 4 and Technical Appendix A of the OESSM: Provided that such sample size shall be chosen for the top 10% of the group at the 95% confidence level for an HCS with a control limit and for the top 10% of the group at the 90% confidence level for an HCS with a recommended limit; and
 - b. carry out the representative measurements at least every 12 months for an HCS with a control limit and at least every 24 months for an HCS with a recommended limit: Provided that whenever the control limit or recommended limit which has been prescribed for an HCS is exceeded, the provisions of regulation 10 shall apply.
3. In order to comply with the provisions of subregulation (1).(e), an employer shall obtain the service of an approved inspection authority who shall, at intervals not exceeding 24 months:
 - a. verify, by examining the measurement and analysis equipment of the employer and questioning the person referred to in subregulation (1).(c), regarding the carrying out of the measurement programme;
 - b. carry out the measurements prescribed by subregulations (1) and (2) for any one group; and

- c. enter the results of the investigation and measurements as contemplated in paragraphs (a) and (b) respectively in the record required by regulation 9.

7. Medical surveillance

1. An employer shall ensure that an employee is under medical surveillance if:
 - a. the employee may be exposed to a substance listed in Table 3 of Annexure 1;
 - b. the exposure of the employee to any substance hazardous to his or her health is such that an identifiable disease or adverse effect to his or her health may be related to the exposure, there is a reasonable likelihood that the disease or effect may occur under the particular conditions of his or her work and there are techniques to diagnose indications of the disease or the effect as far as is reasonably practicable; or
 - c. the occupational health practitioner recommends that the relevant employee should be under medical surveillance in which case the employer may call on an occupational medicine practitioner to ratify the appropriateness of such recommendation.
2. In order to comply with the provisions of subregulation (1) the employer shall, as far as is reasonably practicable, ensure:
 - a. that an initial health evaluation is carried out by an occupational health practitioner immediately before or within 14 days after a person commences employment, where any exposure exists or may exist, which comprises:
 - i. an evaluation of the employees medical and occupational history;
 - ii. a physical examination; and
 - iii. any other essential examination which in the opinion of the occupational health practitioner is desirable in order to enable the practitioner to do a proper evaluation.
 - b. that subsequent to the initial health evaluation contemplated in paragraph (a) the relevant employee undergoes examinations as contemplated in paragraph (a)(ii) and (iii), at intervals not exceeding two years, or at intervals specified by an occupational medical practitioner.

3. An employer shall not permit an employee who has been certified unfit for work by an occupational medicine practitioner to work in a workplace or part of a workplace in which he or she would be exposed: Provided that the relevant employee may be permitted to return to work which will expose him or her if he or she is certified fit for that work beforehand by an occupational medicine practitioner.
4. The employer shall record and investigate the incident contemplated in subregulation (3) in compliance with regulation 8 of the General Administrative Regulations.

8. Respirator zone

An employer shall ensure:

- a. that any workplace or part of a workplace under his or her control, where the concentration of an HCSHCS in the air is, or may be, such that the exposure of employees working in that workplace exceeds the recommended limit without the wearing of respiratory protective equipment, is zoned as a respirator zone;
- b. that a respirator zone is clearly demarcated and identified by notice indicating that the relevant area is a respirator zone and that personal protective equipment as contemplated in regulation 11 must be worn there; and
- c. that no person enters or remains in a respirator zone unless he or she is wearing the required personal protective equipment.

9. Records

1. An employer shall:
 - a. keep records of the results of all assessments, air monitoring, and medical surveillance reports required by regulations 5, 6 and 7, respectively: Provided that personal medical records shall only be made available to an occupational health practitioner;
 - b. subject to the provisions of paragraph (c), make the records contemplated in paragraph (a), excluding personal medical records, available for inspection by an inspector.
 - c. allow any person subject to personal written consent of an employee, to peruse the records with respect to that particular employee;
 - d. make the records of all assessments and air monitoring available for perusal by the relevant health and safety representatives or relevant health and safety committee;

- e. keep all records of assessments and air monitoring for a minimum period of 30 years;
- f. keep all medical surveillance records for a minimum period of 30 years and if the employer ceases activities, all those records shall be handed over or forwarded by registered post to the relevant regional director; and
- g. keep a record of the investigations and tests carried out in terms of regulation 12(1)(b) and of any repairs resulting from these investigations and tests, and the records shall be kept for at least three years.

10. Control of exposure to HCS

1. An employer shall ensure that the exposure of an employee is either prevented or, where this is not reasonably practicable, adequately controlled: Provided that
 - a. where there is exposure for which there is a recommended limit, the control of the exposure shall be regarded as adequate if the level of exposure is below that limit or if the relevant area is zoned and the level of exposure is reduced to below that recommended limit by means of adequate personal protective equipment only after the level has been reduced to as low as is reasonably practicable by any other means than personal protective equipment; or
 - b. where there is exposure for which there is a control limit, the control of the exposure shall be regarded as adequate if the exposure is at a level as low as is reasonably practicable below that control limit: Provided that in the case of temporary excursions above the control limit, the employer shall ensure:
 - i. that the excursion is without a significant risk from exposure;
 - ii. that the excursion is not indicative of a failure to maintain adequate control;
 - iii. that during the excursion, the area is temporarily demarcated as prescribed in regulation 8(b) ; and
 - iv. the provisions of regulation 11 are complied with.
2. Where reasonably practicable, the employer shall control the exposure of an employee:
 - a. by limiting the amount of an HCS used which may contaminate the working environment;

- b. by limiting the number of employees who will be exposed or may be exposed;
 - c. by limiting the period during which an employee will be exposed or may be exposed;
 - d. by using a substitute for an HCS;
 - e. by introducing engineering control measures for the control of exposure, which may include the following:
 - i. Process separation, automation or enclosure;
 - ii. the installation of local extraction ventilation systems to processes, equipment and tools for the control of emissions of an airborne HCS;
 - iii. use of wet methods; and
 - iv. separate workplaces for different processes;
 - f. by introducing appropriate work procedures which an employee must follow where materials are used or processes are carried out which could give rise to exposure of an employee and that procedures shall include written instructions to ensure:
 - i. that an HCS is safely handled, used and disposed of;
 - ii. that process machinery, installations, equipment, tools and local extraction and general ventilation systems are safely used and maintained;
 - iii. that machinery and work areas are kept clean; and
 - iv. that early corrective action can be readily identified.
3. An employer shall ensure that the emission of an HCS into the atmosphere comply with the provisions of the Atmospheric Pollution Prevention Act, 1965 (Act No. 45 of 1965).

11. Personal protective equipment and facilities

- 1. If it is not reasonably practicable to ensure that the exposure of an employee is adequately controlled as contemplated in regulation 10, the employer shall:
 - a. in the case of an airborne HCS, provide the employee with suitable respiratory protective equipment and protective clothing; and

- b. in the case of an HCS which can be absorbed through the skin, provide the employee with suitable non-HCS impermeable protective equipment.
2. Where respiratory protective equipment is provided, the employer shall ensure:
 - a. that the relevant equipment is capable of controlling the exposure to below the OEL for the relevant HCS;
 - b. that the relevant equipment is correctly selected and properly used;
 - c. that information, instructions, training and supervision which is necessary with regard to the use of the equipment is known to the employees; and
 - d. that the equipment is kept in good condition and efficient working order.
3. An employer shall, as far as is reasonably practicable:
 - a. issue no used personal protective equipment to an employee, unless the relevant protection equipment is decontaminated and sterilised;
 - b. provide separate containers or storage facilities for personal protective equipment when not in use; and
 - c. ensure that all personal protective equipment not in use is stored only in the place provided therefor.
4. An employer shall as far as is reasonably practicable, ensure that all contaminated personal protective equipment is cleaned and handled in accordance with the following procedures:
 - a. where the equipment is cleaned on the premises of an employer, care shall be taken to prevent contamination during handling, transport and cleaning;
 - b. where the equipment is sent off the premises to a contractor for cleaning purposes:
 - c. the equipment shall be packed in impermeable containers;
 - d. the containers shall be tightly sealed and have clear indication thereon that the contents thereof are contaminated; and
 - e. the relevant contractor shall be fully informed of the requirements of these regulations and the precautions to be taken for the handling of the contaminated equipment.
5. Subject to the provisions of subregulation (4)(b) an employer shall ensure that no person removes dirty or contaminated personal protective equipment from the premises: Provided that where contaminated personal protective

equipment has to be disposed of, it shall be treated as HCS waste as contemplated in regulation 15.

6. Subject to the provisions of the Facilities Regulations, an employer shall, where reasonably practicable, provide employees using personal protective equipment as contemplated in subregulation (1), with:
 - a. adequate washing facilities which are readily accessible and located in an area where the facilities will not become contaminated, in order to enable the employees to meet a standard of personal hygiene consistent with the adequate control of exposure, and to avoid the spread of an HCS;
 - b. two separate lockers separately labeled 'protective clothing' and 'personal clothing', and ensure that the clothing is kept separately in the locker concerned;
 - c. separate 'clean' and 'dirty' change rooms if the employer uses or processes an HCS to the extent that the HCS could endanger the health of persons outside of the workplace.

12. Maintenance of control measures

An employer shall ensure:

- a. that all control equipment and facilities provided in terms of regulations 10 and 11 are maintained in good working order; and
- b. that thorough examinations and tests of engineering control measures are carried out at intervals not exceeding 24 months by an approved inspection authority or by a person whose ability to do such measurements and tests is verified by an approved inspection authority.

13. Prohibitions

No person shall as far as is reasonably practicable:

- a. use compressed air or permit the use of compressed air to remove particles of an HCS from any surface or person; and
- b. smoke, eat, drink or keep food or beverages in a respirator zone or permit any other person to smoke, eat, drink or keep food or beverages in that zone.

14. Labelling, packaging, transportation and storage

An employer shall, in order to avoid the spread of contamination of an HCS, take steps, as far as is reasonably practicable, to ensure:

- a. that the HCS in storage or distributed are properly identified, classified and handled in accordance with SABS 072 and SABS 0228;
- b. that a container or a vehicle in which an HCS is transported is clearly identified, classified and packed in accordance with SABS 0228 and SABS 0229; and
- c. that any container into which an HCS is decanted, is clearly labelled with regard to the contents thereof.

15. Disposal of hazardous chemical substances

An employer shall, as far as is reasonably practicable:

- a. recycle all HCS waste;
- b. ensure that all collectable HCS waste is placed into containers that will prevent the likelihood of exposure during handling;
- c. ensure that all vehicles, re-usable containers and covers which have been in contact with HCS waste are cleaned and decontaminated after use in such a way that the vehicles, containers or covers do not cause a hazard inside or outside the premises concerned;
- d. ensure that all HCS waste which can cause exposure, is disposed of only on sites specifically designated for this purpose in terms of the Environmental Conservation Act, 1989 (Act No. 73 of 1989), in such a manner that it does not cause a hazard inside or outside the site concerned;
- e. ensure that all employees occupied in the collection, transport and disposal of HCS waste, who may be exposed to that waste, are provided with suitable personal protective equipment; and
- f. ensure that if the services of a waste disposal contractor are used, a provision is incorporated into the contract stating that the contractor shall also comply with the provisions of these regulations.

16. Offences and Penalties

Any person who contravenes or fails to comply with any provision of regulation 3,4,5,6,7,8,9,9A, 10, 11, 12, 13,14 or 15 shall be guilty of an offence and liable on conviction to a fine or to imprisonment for a period not exceeding six months and, in the case of a continuous offence, to an additional fine of R200 for each day on which the offence continues or additional imprisonment of one day for each day on which the offence continuous: Provided that the period of such additional imprisonment shall in no case exceed 90 days.

Annexure 1

HCS Guide Lines

Prevention and Control of Exposure

1. Exposure of employees to substances hazardous to health should be prevented or, where this is not reasonably practicable, adequately controlled. This is a fundamental requirement of the Regulations for Hazardous Chemical Substances (HCS), 1995. Exposure can occur by inhalation, ingestion or absorption through the skin, but inhalation is usually the main route of entry into the body. Tables 1 and 2 of Annexure 1 list the occupational exposure limits, which should be used in determining the adequacy of control of exposure by inhalation, as required by the HCS Regulations.
2. The advice in this document should be taken in the context of the requirements of the HCS Regulations, especially regulation 5 (Assessment of potential exposure), regulation 10 (Control of exposure), regulation 12 (Maintenance of control measures) and regulation 6 (Air monitoring). Substances hazardous to health are defined in regulation 1. There is separate legislation for lead and asbestos and these substances are not covered in detail in this document. This document also does not apply to exposure below ground in mines or exposure to micro-organisms.
3. Adequate control of exposure (when prevention is not reasonably practicable) should be achieved by one or more of a range of control measures described in regulation 10 of the HCS Regulations. Control by personal protective equipment should be applied only when other means are not reasonably practicable.

Medical Surveillance

4. Medical surveillance of employees is often an important addition to the control measures in the workplace, regulation 7(1) of the HCS Regulations specifies where medical surveillance is appropriate for the protection of the health of employees.

4.1 Medical surveillance is defined in the Regulations to cover the spectrum of potential effects of an HCS on an employee, from absorption of the substances through to clinical disease. Medical surveillance may be grouped broadly into-

- a. biological monitoring, to measure the extent of absorption of an HCS by the employee.
- b. medical screening, to detect any adverse affects of an HCS on the employee.

4.2 BIOLOGICAL MONITORING OF EXPOSURE

4.2.1 Objectives

Biological monitoring of exposure can be divided into two types of testing:

- a. Biological monitoring: Measures the bio-chemical concentrations of HCSs and/or their metabolites in biological samples of exposed individuals, e.g. blood lead for inorganic lead exposure, or urinary arsenic for inorganic arsenic exposure. The aim is to measure the degree of absorption into the body by measuring indicators in representative biological samples, typically urine or blood (usually not related to the target organ).
- b. Biological effect monitoring: Determines the intensity of biochemical or physiological change due to exposure, e.g. red cell cholinesterase for exposure to organophosphate pesticides, or zinc protoporphyrin (ZPP) for exposure to inorganic lead.

4.2.2 Uses of biological monitoring

Biological monitoring tests are indices of an individual's exposure and they may be a useful tool for the occupational health and safety team. They give information on the overall level of exposure, regardless of whether an HCS has been absorbed by the respiratory, oral, or cutaneous route. Cutaneous absorption can play a significant role in the case of some organic compounds. The amounts absorbed through the skin may be comparable to or even higher than those absorbed via the respiratory tract.

Where appropriate, environmental control measures may thus be supplemented, with biological monitoring. Knowledge of the real individual exposure permits targeted applications of preventive measures.

4.2.3 Important considerations in biological monitoring

- a. In choosing a test to meet the above objectives, it is important to have an understanding of the relationship between environmental exposure and the concentration of an HCS in biological samples. This includes an understanding of the principles of absorption, biotransformation, distribution and excretion of an HCS.
- b. In addition, there should be analytical methods available of sufficient sensitivity and specificity to detect concentrations of the substance in urine, blood or exhaled air in the range likely to be encountered in industry.
- c. The HCSs listed in Table 3 of Annexure 1 are those for which the above criteria have a reasonable chance of being met.

4.2.4 Biological Exposure Indices (BEIs)

BEIs are reference values intended as guidelines for the evaluation of potential health hazards in the practice of industrial hygiene. A BEI represents in theory the level of an HCS or metabolite most likely to be observed in a specimen collected from a healthy worker who has been exposed to an HCS to the same extent as the worker with inhalation exposure to an OEL-TWA. BEIs do not represent a sharp distinction between hazardous and non-hazardous exposures. For example, owing to biological variability, it is possible that an individual's measurements can exceed the BEI without incurring an increased health risk. Conversely, there may be some susceptible individuals who may be harmed at effects below the BEI.

If measurements in specimens obtained from a worker on different occasions persistently exceed the BEI, or if the majority of measurements in specimens obtained from a group of workers at the same workplace exceed the BEI, the cause of the excessive values must be investigated and proper action be taken to reduce the exposure.

BEIs apply to eight-hour exposures, five days a week. However, BEIs for differing work schedules may be extrapolated on pharmacokinetic grounds. BEIs should not be applied either directly or through a conversion factor, in the determination of safe levels for non-occupational exposure to air and water pollutants, or food contaminants. The BEIs are not intended for use as a measure of adverse effects or for diagnosis of occupational illness.

4.3 MEDICAL SCREENING

4.3.1 Objectives

- a. The principle of general medical screening is to detect a disease at an early subclinical or presymptomatic stage in order to take action to reverse these effects or to slow progression of the disease. The abnormalities sought, include pathophysiological or histopathological changes. Such tests are well-established in general preventative medicine, e.g. PAP smears for cervical cancer, cholesterol screening, faecal occult blood for lower bowel cancer, etc.
- b. In medical surveillance in industry one is interested not only in detecting adverse effects in the individual, but also in the implication of the findings for the effectiveness of workplace control measures., Medical surveillance is thus directed not only at early adverse effects but also at established disease.

4.3.2 Types of examination

- a. The number of validated screening tests with regard to HCSs is smaller than in general preventive medicine, but is likely to grow in the future. Examples of subclinical tests include urinary cytology for bladder cancer among workers exposed to potential bladder carcinogens, or full blood counts for employees exposed to an HCS toxic for the bloodforming organs.
- b. Medical surveillance may include simple clinical examination, such as examination of the skin of employees exposed to contact irritants or allergens, or of the nasal septum of employees exposed to chromates.
- c. Chest X-rays for silicosis are an example of screening for irreversible (although potentially progressive) disease. Lung function testing is well established as a non-specific test for the possible effect of respiratory irritants, sensitisers and fibrogenic agents.

4.4 DESIGNING AND IMPLEMENTING A PROGRAMME OF MEDICAL SURVEILLANCE

4.4.1 The following steps should be included in any programme:

- a. Risk assessment to determine the potential exposure to and routes of absorption of an HCS, as required by regulation 5.
- b. Identification of target-organ toxicity, so as to direct medical screening.

- c. Selection of appropriate tests and testing schedule. Tests should have the desirable operating characteristics of high sensitivity, specificity, reliability and predictive value. The frequency of testing is laid down in general terms by regulation 7(2) , but should in any case be based on an understanding of the nature of the hazard and the natural history of any adverse effects.
- d. Development of action criteria. These are provided for some HCSs in the form of BEIs in Table 3 of Annexure 1. Criteria for interpreting lung function testing have also been published in the medical literature. However, in many cases, the occupational health practitioners will have to develop pragmatic criteria in the context of the specific workplace.
- e. Standardisation of test process. Quality control needs to be exercised both in the testing site and in the laboratory contracted to carry out analyses. Consistency over time should be sought so as to make longitudinal measurements comparable.
- f. Ethical considerations. Information and training of employees as required by regulation 3 (1) should include the rationale for doing medical surveillance, and the consequence of abnormal findings. An employee must be notified of the results and interpretation of his/her tests and any recommendations made. The confidentiality of personal medical records is laid down by regulation 9.
- g. Determination of employees fitness to remain in that job. [Regulation 7(3)]. Results may be compared against the action criteria (BEI if relevant), and preferably also the employees previous results to determine whether individual action needs to be taken. Action may include repeating the test, further medical examination, removal of the employee from further exposure, and notification of the employer. Co-operation of employees can be best secured by a policy of protection of conditions of service in case of medical removal from a particular job.
- h. Evaluation of control. An abnormal finding in an employee, or a pattern of findings in a group of employees, may point to inadequate primary control of exposure. In such cases the employer needs to be notified of such details of the medical findings as are necessary to evaluate the workplace problem and take remedial action.
- i. Record keeping. This includes both medical records and exposure information for every employee. While the employer is responsible for record keeping in terms of regulation 9, the contents of personal medical records may be accessible to the occupational medicine practitioner, the employee, and any person nominated by the employee in writing.

4.4.2 The onus is on the occupational health practitioner carrying out medical surveillance to be familiar with the latest scientific information regarding the HCS and tests that might be useful. The aim should be to design a programme that is rational, ethical and effective. This may have to be done in the face of incomplete information of uncertainty regarding exposures, toxicity and test performance.

Legal Background to Exposure Limits

5. Two types of occupational exposure limits are defined in regulation 1 of the HCS Regulations. The two types are occupational exposure limit - control limit (OEL-CL), and occupational exposure limit - recommended limit (OEL-RL), as listed in Tables 1 and 2 of Annexure 1 (Table 1) (Table 2). The key difference between the two types of limits is that one OEL-RL is set at a level at which there is no indication of a risk to health; for an OEL-CL, a residual risk may exist and the level set, takes socio-economic factors into account. Further details are given in paragraphs 8 to 16.

6. Regulation 10 of the HCS Regulations lays down the requirements for the use of an OEL-CL and an OEL-RL for HCS for the purpose of achieving adequate control. Regulation 10(1) requires that, where there is exposure to a substance for which an OEL-CL is specified in Table 1 of Annexure 1, the control of exposure shall, so far as inhalation of that substance is concerned, be treated as adequate only if the level of exposure is reduced so far as is reasonably practicable and in any case below the OEL-CL..

7. Regulation 10(1) of the HCS Regulations requires that, where there is exposure to a substance for which an OEL-RL has been approved, the control of exposure shall, so far as inhalation of that substance is concerned, be treated as adequate if-

- a. that OEL-RL is not exceeded; or
- b. where that OEL-RL is exceeded, the employer identifies the reasons for the exceeding of the standard and takes appropriate action to remedy the situation as soon as is reasonably practicable.

Setting Occupational Exposure Limits

ADVISORY COUNCIL AND STANDING TECHNICAL COMMITTEE

8. OEL-RL and OEL-CL are set by the chief inspector on recommendation of the Advisory Council for Occupational Health and Safety (the Advisory Council), following assessment by the Standing Committee No. 7 (TC7) of the Advisory Council for Occupational Health and Safety.

9. TC 7 must first consider what type of limit is appropriate, OEL-RL, or OEL-CL, and secondly, at what concentration the limit should be set. Setting an OEL-RL is the first option to be considered and TC 7 comes to a decision based on a scientific judgment of the available information on health effects. If, however, TC 7 decides that an OEL-CL is more appropriate, consideration of the level at which to set the limit passes to the Advisory Council, since it involves socio-economic judgments, balancing risk to health against the cost and effort of reducing exposure. Following public consultation, new OEL-CLs and OEL-RLs are listed in Table 1 and Table 2 of Annexure 1 respectively with the approval of the chief inspector.

THE INDICATIVE CRITERIA

10. An OEL-RL can be assigned to a substance, if all three of the following criteria are complied with:

There is a no-risk at the exposure limit

Criterion 1: The available scientific evidence allows for the identification, with reasonable certainty, of a concentration averaged over a reference period, at which there is no indication that the substance is likely to be injurious to employees if they are exposed by inhalation day after day to that concentration.

Likely excursions above the exposure limit are unlikely

Criterion 2: Exposure to concentrations higher than that derived under criterion 1 and which could reasonably occur in practice, is unlikely to produce serious short or long-term effects on health over the period of time it might reasonably be expected to take to identify and remedy the cause of excessive exposure.

Compliance is reasonably practicable

Criterion 3: The available evidence indicates that compliance with an OEL-RL, as derived under criterion 1, is reasonably practicable.

11. A substance which does not meet criteria 1, 2 and 3, can be assigned an OEL-CL and must meet either of the following criteria:

Criterion 4: The available evidence on the substance does not satisfy criterion 1 and/or 2 for an OEL-RL and exposure to the substance has, or is liable to have, serious health implications for workers; or

Criterion 5: Socio-economic factors indicate that although the substance meets criteria 1 and 2 for an OEL-RL, a numerically higher value is necessary if the controls associated with certain uses are to be regarded as reasonably practicable.

SETTING AN OEL-RL

12. Criterion 1 sets out the fundamental basis for establishing such a limit: The existence of a threshold above which there may be evidence of significant effects on health but below which, on existing knowledge, there are thought to be no adverse effects.

13. Criterion 2 is necessary in order to take account of HCS Regulation 10 (1) of the HCS Regulations whereby exposures above an OEL-RL are allowed provided the employer identifies the reasons for exceeding the standard and takes steps to reduce exposure to that OEL-RL as soon as is reasonably practicable. Clearly, it is necessary to take account of the likelihood and probable extent of cases in deciding whether an OEL-RL is appropriate. The health effects to be taken into account include sensory and other effects such as the slowing of reflexes which might result in the impairment of safety.

14. Criterion 3 takes account of whether industry can reasonably comply with the exposure limit derived under the first criterion. There is no purpose in setting an OEL-RL which plainly cannot be achieved in practice. Note that industry's ability to comply, influences the decision of whether to set an OEL-RL, but does not influence the level at which that OEL-RL is set.

SETTING AN OEL-CL

15. To be assigned an OEL-RL, a substance must meet all the first three criteria; if it does not, then it can be considered for an OEL-CL. To be assigned an OEL-CL, there should be serious implications for the health of workers exposed to the substance. Serious health implications include both the risk of serious health effects to a small population of workers and the risk of relatively minor health effects to a large population. In practice, an OEL-CL has been most often allocated to carcinogens and to other substances for which no threshold of effect can be identified and about which there is no doubt about the seriousness of the effects of exposure.

16. An OEL-CL and an OEL-RL, therefore, differ not only in their legal status, but also in the way in which they are set. For an OEL-RL the only consideration in setting the limits is the protection of the health of the employee; for an OEL-CL this is still the primary consideration but socio-economic factors are also taken into account.

17. The indicative criteria, then, provide the framework within which the discussions at the various stages of limit-setting can be conducted.

Applying Occupational Exposure Limits

GENERAL

18. The lists of occupational exposure limits given in Table 1 and Table 2 of Annexure 1, unless otherwise stated, relate to personal exposure to substances hazardous to health in the air of the workplace.

UNITS OF MEASUREMENT

19. In occupational exposure limits, concentrations of gases and vapours in air are usually expressed in parts per million (ppm), a measure of concentration by volume, as well as in milligrams per cubic metre of air (mg/m^3), a measure of concentration by mass. In converting from ppm to mg/m^3 a temperature of 25°C and an atmospheric pressure of 101.325 kPa are used. Concentrations of airborne particles (fume, dust, etc.) are usually expressed in mg/m^3 . In the case of dust, the limits in the tables refer to the total inhalable fraction unless specifically indicated as referring to the respirable fraction (see paragraph 36). In the case of a man-made mineral fibre, the limit is expressed as fibres per millilitre of air (fibres/ml).

OCCUPATIONAL EXPOSURE LIMITS - CONTROL LIMITS; CL 9TABLE 1)

20. An OEL-CL is the maximum concentration of an airborne substance, averaged over a reference period, to which employees may be exposed by inhalation under any circumstances, and is specified together with the appropriate reference period in Table 1 of Annexure 1.

21. Regulation 19(1) of the HCS Regulations, when read in conjunction with the Act, imposes a duty on the employer to take all reasonable precautions and to exercise all due diligence to ensure that exposure is kept as far below an OEL-CL as is reasonably practicable.

22. To comply with this duty, in the case of substances with a 8-hour reference period, employers should undertake a programme of monitoring in accordance with regulation 6 so that they can show (if it is the case), that an OEL-CL is not exceeded. Such a monitoring programme need not be undertaken if the assessment carried out in accordance with regulation 5 shows that the level of exposure is most unlikely ever to exceed an OEL-CL. For substances assigned a short-term limit, such value should never be exceeded.

23. The assessment should also be used to determine the extent to which it is reasonably practicable to reduce exposure further below an OEL-CL as required by regulation 10 (1) In assessing reasonable practicability, the nature of the risk presented by the substance in question should be weighed against the cost and the effort involved in taking measures to reduce the risk. (Also see the definition of reasonably practicable as defined in the Act.)

OCCUPATIONAL EXPOSURE LIMIT-RECOMMENDED LIMIT;OEL-RL (TABLE 2)

24. An OEL-RL is the concentration of an airborne substance, averaged over a reference period, at which, according to current knowledge, there is no evidence that it is likely to be injurious to employees if they are exposed by inhalation, day after day, to that concentration.

25. For a substance, which has been assigned an OEL-RL, exposure by inhalation should be reduced to that standard. However, if exposure by inhalation exceeds the OEL-RL, then control will still be deemed to be adequate provided that the employer has identified why the OEL-RL has been exceeded and is taking appropriate steps to comply with the OEL-RL as soon as reasonably practicable. In such a case, the employer's objective must be to reduce exposure to the OEL-RL, but the final achievement of this objective may take some time. The assessment under regulation 5 will determine the urgency of the necessary action, taking into account the extent and cost of the required measures in relation to the nature and degree of exposure involved.

26. Control of an OEL-RL as prescribed in regulation 10 (1) (a) can always be regarded as adequate control of that substance for the purpose of the HCS Regulations, so far as exposure from inhalation is concerned. However, due to the variations in process control and the fluctuations in substance concentrations in the workplace, it will be prudent for employers to reduce exposure below an OEL-RL as to ensure that the exposure of all employees does not exceed that OEL-RL. Similarly, it is not intended that the statutory requirements under regulation 10 (1) should discourage the further application of good occupational hygiene principles in order to reduce exposure below the OEL-RL.

LONG-TERM AND SHORT-TERM EXPOSURE LIMITS

27. The pattern of effects due to exposure to substances hazardous to health varies considerably depending on the nature of the substance and the exposure. Some effects require prolonged or accumulated exposure. The long-term (8-hour time weighted average) exposure limit is intended to control such effects by restricting the total intake by inhalation over one or more workshifts. Other effects may be seen after brief exposures which have occurred once or repeatedly. Short-term limits (usually 15 minute) may be applied to such substances. Where long-term limits also apply, the short-term limits restrict the magnitude of excursion above the average concentration during longer exposures. For those substances for which no short-term limit is specified, it is recommended that a figure of three times the long-term limit be used as a guideline for controlling short-term excursions in exposure. With some other substances, brief exposure may be critical and the exposure limit necessary to prevent these excursions will also control any other effects. A separate long-term limit is not considered necessary in such cases and the short-term limit applies throughout the shift.

28. Exposure limits are expressed as airborne concentrations averaged over a specified period of time. The period for the long-term limit is normally eight hours. When a different period is used, this is stated. The averaging period for the short-term exposure limit is normally 15 minutes. Such a limit applies to any 15 minute period throughout the working shift.

LIMITATIONS TO THE APPLICATION OF EXPOSURE LIMITS

29. The exposure limits relate to personal exposure with the exception of the annual OEL-CL for vinyl chloride which should be recorded as the time-weighted average of vinyl chloride in the atmosphere of a working place over a period of one year (see Annexure 2 and the OEL-RL for cotton dust is not a personal exposure standard, but a static air standard (see Annexure 4).

30. The limits cannot readily be extrapolated to evaluate or control non-occupational exposure, e.g. levels of contamination in the neighbourhood close to an industrial plant. OELs only apply to persons at work. Employers should also take into account their duties under the Environmental Protection Act. The OELs are also only approved for use where the atmospheric pressure is between 85 kPa and 101.325 kPa. This covers the normal range of meteorological variations and slightly pressurised workplaces such as cleaning rooms, but not the higher pressures that may be encountered in, for example, tunnelling or underwater hyperbaric chambers. Such situations require special assessments.

31. Occupational exposure limits, as set out in Tables 1 and 2 of Annexure 1, are intended to be used for normal working conditions in workplaces. Employers should also take into account their duties and the provisions of the Environmental Conservation Act. OELs are not, however, designed to deal with serious accidents or emergencies, particularly where employees may be exposed to rapidly rising concentrations of gas, as may arise from a major escape due to plant failure. Over and above their responsibilities to ensure that the requirements of the HCS Regulations are met, employers also have a clear responsibility to ensure that the plant is designed, operated and maintained in a way that avoids accidents and emergencies. Where appropriate, detection, alarm and response measures should be used in order to minimise the effect of any such unplanned events.

32. To help maintain adequate operational control, employers may find it helpful to select their own indicators of control when undertaking investigations or corrective action.

EXPOSURE IN MINES

33. The HCS Regulations and the occupational exposure limits in this publication do not apply to exposure to substances hazardous to health in mines.

LEAD AND ASBESTOS

34. Work with asbestos or lead is not subject to the HCS Regulations. The exposure limits for various types of asbestos and lead are specified in the Asbestos Regulations and the Lead Regulations.

PESTICIDES

35. Substances used as active ingredients in pesticides are listed under their chemical names and/or their common (ISO) names. These names may sometimes be used as parts of the names of proprietary pesticide formulations. In all cases the exposure limit applies to the specific active ingredients and not to the formulation as a whole.

DUSTS

36. The general approach necessary to control occupational exposure to dusts is as follows: not all dusts have been assigned occupational exposure limits but the lack of such limits should not be taken to imply an absence of hazard. In the absence of a specific exposure limit for a particular dust, exposure should be adequately controlled. Where there is no indication of the need for a lower value, personal exposure should be kept below both 10 mg/m³ 8-hour time-weighted average total inhalable dust and 5 mg/m³ time-weighted average respirable dust. Such, or greater, dust concentrations should be taken as the substantial concentrations. A substantial concentration of dust should be taken as a concentration of 10 mg/m³, 8-hour time-weighted average, of respirable dust, where there is no indication of the need for a lower value, and as such they are referred to as substances hazardous to health.

TOTAL INHALABLE DUST AND RESPIRABLE DUST

37. Total inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction which penetrates to the gas exchange region of the lung. A fuller definition is given at the end of Table 2 of Annexure 1 (Abbreviations). (reproduced below)

The concentration of respirable dust shall be determined from the fraction passing a size selector with an efficiency that will allow:

- i. 100% of particles of 1 mm aerodynamic diameter
- ii. 50% of particles of 5 mm aerodynamic diameter
- iii. 20% of particles of 6 mm aerodynamic diameter

iv. 0% of particles of 7 mm aerodynamic diameter and larger to pass through the size selector.

38. Where dusts contain components which have their own assigned occupational exposure limits, all the relevant limits should be complied with.

FUME

39. Where a separate OEL has been set for fume, it should normally be applied to solid particles generated by chemical reactions or condensed from the gaseous state, usually after volatilisation from melted substances. The generation of fume is often accompanied by a chemical reaction such as oxidation or thermal breakdown.

ABSORPTION THROUGH THE SKIN

40. In general, for most substances the main route of entry into the body is by inhalation. The OELs given in these regulations solely relate to exposure by this route. Certain substances such as phenol, aniline and certain pesticides (marked in the Tables with an SK notation) have the ability to penetrate the intact skin and thus become absorbed into the body. Absorption through the skin can result from localised contamination, for example, from a splash on the skin or clothing, or in certain cases from exposure to high atmospheric concentrations of vapour. Serious effects can result in little or no warning and it is necessary to take special precautions to prevent skin contact when handling these substances. Where the properties of the substances and the methods of use provide a potential exposure route via skin absorption, these factors should be taken into account in determining the adequacy of the control measures.

SENSITISERS

41. Certain substances may cause sensitisation of the respiratory tract if inhaled or skin contact occurs. Respiratory sensitisers can cause asthma, rhinitis, or extrinsic allergic alveolitis. Skin sensitisers cause allergic contact dermatitis. Substances which cause skin sensations are not necessarily respiratory sensitisers or vice-versa. Only a proportion of the exposed population will become sensitised, and those who do become sensitised, will not have been identified in advance. Individuals who become sensitised may produce symptoms of ill health after exposure even to minute concentrations of the sensitiser.

42. Where it is reasonably practicable, exposure to sensitisers should be prevented. Where this cannot be achieved, exposure should be kept as low as is reasonably practicable and activities giving rise to short-term peak-concentrations should receive particular attention. As with other substances, the spread of contamination by sensitisers to other working areas should also be prevented, as far as is reasonably practicable.

43. The Sen notation (marked in the Tables with a Sen notation) has been assigned only to those sensitizers that may cause sensitization by inhalation. Remember that other substances not contained in these Tables can act as respiratory sensitizers.

OTHER FACTORS

44. Working conditions which impose additional stress on the body, such as exposure to ultra-violet radiation, high temperatures, pressures and humidity, may increase the toxic response to a substance. In such cases, specialist advice may be necessary to evaluate the effect of these factors.

Mixed Exposures

GENERAL

45. The majority of OELs listed in Tables 1 and 2 of Annexure 1 are for single compounds or for substances containing a common element or radical, e.g. tungsten and compounds, and isocyanates. A few of the limits relate to substances commonly encountered as complex mixtures or compounds e.g. white spirit, rubber fume, and welding fume. However, workers are frequently subject to other mixed exposures involving solids, liquids, aerosols or gases. These exposures can arise as a result of work with materials containing a mixture of substances, or from work with several individual substances, simultaneously or successively, in a workshift. Mixed exposures require careful assessment of their health effects and the appropriateness of control standards. The following paragraphs provide a brief summary of the advice on the application of exposure limits in these circumstances. In all cases of doubt, specialist advice should be sought.

EFFECTS OF MIXED EXPOSURES

46. The ways in which the constituent substances of a mixed exposure interact, vary considerably. Some mixed exposures involve substances that act on different body tissues or organs, or by different toxicological mechanisms, these various effects being independent of each other. Other mixtures will include substances that act on the same organs, or by similar mechanisms, so that the effects reinforce each other and the substances are additive in their effect. In some cases the overall effect is considerably greater than the sum of the individual effects and the system is synergistic. This may arise from mutual enhancement of the effects of the constituents or because one substance potentiates another, causing it to act in a way which it would not do alone.

ASSESSMENT AND CONTROL

47. With All types of mixed exposures, it is essential that assessments be based on the concentrations of each of the constituents in air to which workers are exposed. Depending on the nature of the constituents and the circumstances of use, the relative concentrations of the constituents in air may differ considerably from those in the liquid or solid source material. The composition of the bulk material should not be relied on for assessment unless there is good evidence for doing so.

48. Where mixed exposures occur, the first step is to ensure adequate control of exposure for each individual substance. However, the nature and amount of the other substances in a mixture can influence the level to which it is reasonably practicable to reduce exposure to a substance subject to an OEL-CL. When limits for specific mixtures have been established, they should be used only where they are applicable, and in addition to any relevant individual limits. They should not be extended to inappropriate situations. It is then necessary to assess whether further control is needed to counteract any increased risk from the substances acting in conjunction. Expert assessments for some particular mixed exposures may be available and can be used as guidelines in similar cases. In other cases, close examination of the toxicological data will be necessary to determine which of the main types of interaction (if any) are likely for the particular combination of substances concerned. The various types should be considered in the following order:

a. Synergistic substances: Known cases of synergism and potentiation are considerably less common than the other types of behaviour in mixed exposures. However, they are the most serious in their effects and require the most strict control. They are also the most difficult to assess and wherever there is reason to suspect such interaction, specialist advice should be obtained;

b. Additive substances: Where there is reason to believe that the effects of the constituents are additive, and where the exposure limits are based on the same health effects, the mixed exposure should be assessed by means of the formula—here C1, C2, etc. are the time-weighted average (TWA) concentrations of constituents in air and L1, L2, etc. are the corresponding exposure limits. The use of this formula is only applicable where the additive substances have been assigned OELs, and L1, L2, etc. relate to the same reference period in the list of approved OELs. Where the sum of the C/L fractions does not exceed one, the exposure is considered not to exceed the national OELs. If one of the constituents has been assigned an OEL-CL, then the additive effect should be taken into account in deciding the extent to which it is reasonably practicable to further reduce exposure; and

c. Independent substances: Where no synergistic or additive effects are known or considered likely, the constituents can be regarded as acting independently. It is then sufficient to ensure compliance with each of the OELs individually.

49. The above steps provide basic protocol for assessment of mixed exposures. It is open to persons responsible for control of exposure to treat all non-

synergistic systems as though they were additive. This avoids the need to distinguish additive and independent systems and can be regarded as the most prudent course, particularly where the toxicity data are scarce or difficult to assess.

MONITORING MIXED EXPOSURE

50. Further information on monitoring airborne contaminants is given in paragraphs 52 and 53. The number of components of a mixed exposure for which routine air monitoring is required, can be reduced if their relative concentrations can be shown to be constant. This involves the selection of a key or marker, which may be one of the constituents, as a measure of the total contamination. Exposure to the marker is controlled at a level selected so that exposures to all components will be controlled in accordance with the criteria in paragraphs 48(a) and (b). However, if one of the components has been assigned an OEL-CL, the level of the exposure to that substance should always be reduced as far as is reasonably practicable. If this approach is to be used, it should take place under the guidance of suitable specialist advice.

COMPLICATING FACTORS

51. Several factors that complicate the assessment and control of exposure to individual substances will also affect cases of mixed exposures and will require similar special consideration. Such factors include-

- a. exposure to a substance for which there is no established limit or for which an OEL-CL has been set;
- b. the relevance of factors such as alcohol, medication, smoking and additional stresses;
- c. exposure of the skin to one or more substances that can be absorbed by this route, as well as by inhalation; and
- d. substances in mixture may mutually affect the extent of their absorption, as well as their health effects, at a given level of exposure.

Biological Exposure Indices

Acetone

Determinant	Acetone in urine
Sampling Time	End of shift
BEI	100 mg/l
Notation	B , C

Aniline

Determinant	Total p-aminophenol in urine
Sampling Time	End of shift
BEI	50 mg/g creatinine
Notation	C

Determinant	Methemoglobin in blood
Sampling Time	During or end of shift
BEI	1.5% of hemoglobin
Notation	B, C , D

Arsenic and soluble compounds, including Arsine

Determinant	Inorganic arsenic metabolites in urine
Sampling Time	End of workweek
BEI	50 ug/g creatinine
Notation	B

Benzene

Determinant	Total phenol in urine
Sampling Time	End of shift
BEI	50 mg/g creatinine
Notation	B, C

Benzene in exhaled air:

Determinant	Mixed exhaled
Sampling Time	Prior to next shift
BEI	0.08 ppm
Notation	D

Determinant	End exhaled
BEI	0.12 ppm

Cadmium

Determinant	Cadmium in urine
Sampling	Not critical

Time**BEI** 10 ug/g creatinine**Notation** B**Determinant** Cadmium in blood**Sampling** Not critical**Time****BEI** 10 ug/l**Notation** B**Carbon Disulphide****Determinant** 2-Thiothiazolidine-4-carboxylic acid (TTCA) in urine**Sampling** End of shift**Time****BEI** 5 mg/g creatinine**Carbon Monoxide****Determinant** Carboxyhemoglobin in blood**Sampling** End of shift**Time****BEI** < 8 % of hemoglobin**Notation** B, C**Determinant** CO in end exhaled air**Sampling** End of shift**Time****BEI** < 40 ppm**Notation** B, C**Chlorobenzene****Determinant** Total 4-chlorocatechol in urine**Sampling** End of shift**Time****BEI** 150 mg/g creatinine**Notation** C**Determinant** Total p-chlorophenol in urine**Sampling** End of shift**Time****BEI** 25 mg/g creatinine**Notation** C**Chromium (VI)****Determinant** Water soluble fume**Sampling** Increase during shift**Time****BEI** 10 ug/g creatinine**Notation** B**Determinant** Total chromium in urine**Sampling** End of shift at end of workweek**Time**

BEI 30 ug/g creatinine
Notation B

N,N-Dimethylformamide (DMF)

Determinant N-Methylformamide in urine
Sampling Time End of shift
BEI 40 mg/g creatinine
Notation B

2-Ethoxyethanol (EGEE)

Determinant 2-Ethoxyacetic acid in urine
Sampling Time End of shift at end of workweek
BEI 100 mg/g creatinine

2-Ethoxyethylacetate (EGEEA)

Determinant 2-Ethoxyacetic acid in urine
Sampling Time End of shift at end of workweek
BEI 100 mg/g creatinine

Ethyl Benzene

Determinant Mandelic acid in urine
Sampling Time End of shift at end of workweek
BEI 1.5 g/g creatinine
Notation A

Determinant Ethyl benzene in end exhaled air
Notation D

Flourides

Determinant Flourides in urine
Sampling Time Prior to shift
BEI 3 mg/g creatinine
Notation B, C

Sampling Time End of shift
BEI 10 mg/g creatinine
Notation B, C

Furfural

Determinant Total furoic acid in urine
Sampling Time End of shift
BEI 200 mg/g creatinine
Notation B, C

n-Hexane

Determinant 2,5-Hexanedione in urine
Sampling Time End of shift
BEI 5 mg/g creatinine
Notation C

Determinant n-Hexane in end-exhaled air
Notation D

Lead

Determinant Lead in blood
Sampling Time Not critical
BEI 50 ug/100 ml
Notation B

Determinant Lead in urine
Sampling Time Not critical
BEI 150 ug/g creatinine
Notation B

Determinant Zinc protoporphyrin in blood
Sampling Time After 1 month exposure
BEI 250 ug/100 ml erythrocytes or 100 ug/100ml blood
Notation B

Mercury

Determinant Total inorganic mercury in urine
Sampling Time Preshift
BEI 35 ug/g creatinine
Notation B

Determinant Total inorganic mercury in blood
Sampling Time End of shift at end of workweek
BEI 15 ug/l
Notation B

Methanol

Determinant Methanol in urine
Sampling Time End of shift
BEI 15 mg/l
Notation B, C

Determinant Formic acid in urine
Sampling Time Prior to last shift of workweek

Time**BEI** 80 mg/g creatinine**Notation** B, C**Methemoglobin inducers****Determinant** Methemoglobin in blood**Sampling Time** During or end of shift**BEI** 1.5% of hemoglobin**Notation** B, C, D**Methyl Chloroform****Determinant** Methyl chloroform in end exhaled air**Sampling Time** Prior to last shift of workweek**Time****BEI** 40 ppm**Determinant** Trichloroacetic acid in urine**Sampling Time** End of workweek**Time****BEI** 10 mg/l**Notation** C, D**Determinant** Total trichloroethanol in urine**Sampling Time** End of shift at end of workweek**Time****BEI** 30 mg/l**Notation** C, D**Determinant** Total trichloroethanol in blood**Sampling Time** End of shift at end of workweek**Time****BEI** 1 mg/l**Notation** C**Methyl Ethyl Ketone (MEK)****Determinant** MEK in urine**Sampling Time** End of shift**Time****BEI** 2 mg/l**Methyl isobutyl ketone (MIBK)****Determinant** MIBK in urine**Sampling Time** End of shift**Time****BEI** 2 mg/l**Nitrobenzene****Determinant** Total p-nitrophenol in urine**Sampling Time** End of shift at end of workweek**Time****BEI** 5 mg/g creatinine

Notation	C
Determinant	Methemoglobin in blood
Sampling Time	End of shift
BEI	1.5% of hemoglobin
Notation	B, C , D

Organophosphorus Cholinesterase Inhibitors

Determinant	Cholinesterase activity in red cells
Sampling Time	Discretionary
BEI	70% of individual's baseline
Notation	B, C , D

Parathion

Determinant	Total p-nitrophenol in urine
Sampling Time	End of shift
BEI	0.5 mg/g creatinine
Notation	C , D

Determinant	Cholinesterase activity in red cells
Sampling Time	Discretionary
BEI	70% of individuals baseline
Notation	B, C , D

Pentachlorophenol

Determinant	Total PCP in urine
Sampling Time	Prior to the last shift of workweek
BEI	2 mg/g creatinine
Notation	B

Determinant	Free PCP in plasma
Sampling Time	End of shift
BEI	5 mg/l
Notation	B

Perchloroethylene

Determinant	Perchloroethylene in end-exhaled air
Sampling Time	Prior to the last shift of workweek
BEI	10 ppm
Determinant	Perchloroethylene in blood
Sampling Time	Prior to the last shift of workweek
BEI	1 mg/l

Determinant Trichloroacetic acid in urine
Sampling Time End of workweek
BEI 7 mg/l
Notation C , D

Phenol

Determinant Total phenol in urine
Sampling Time End of shift
BEI 250 mg/g creatinine
Notation B, C

Styrene

Determinant Mandelic acid in urine
Sampling Time End of shift
BEI 800 mg/g creatinine
Notation C

Sampling Time Prior to next shift
BEI 300 mg/g creatinine
Notation C

Determinant Phenolglyoxylic acid in urine
Sampling Time End of shift
BEI 240 mg/g creatinine
Notation B, C

Sampling Time Prior to next shift
BEI 100 mg/g creatinine
Notation B, C

Determinant Styrene in venous blood
Sampling Time End of shift
BEI 0.55 mg/l
Notation D

Sampling Time Prior to next shift
BEI 0.02 mg/l
Notation DD

Toluene

Determinant Hippuric acid in urine
Sampling Time End of shift Last 4 hours of shift

BEI 2.5 g/g creatinine
Notation B, C

Determinant Toluene in venous blood
Sampling Time End of shift

BEI 1 mg/l
Notation D

Determinant o-Cresol in urine
Sampling Time End of shift

BEI 1 mg/g creatinine
Notation C

Trichloroethylene

Determinant Trichloroacetic acid in urine
Sampling Time End of workweek

BEI 100 mg/g creatinine
Notation C

Determinant Trichloroacetic acid and trichloroethanol in urine
Sampling Time End of shift at end of workweek

BEI 300 mg/g creatinine
Notation C

Determinant Free trichloroethanol in blood
Sampling Time End of shift at end of workweek

BEI 4 mg/l
Notation C

Determinant Trichloroethylene in end-exhaled air
Notation D

Xylenes

Determinant Methylhippuric acid in urine
Sampling Time End of shift Last 4 hours of shift

BEI 1.5 g/g creatinine
Notation 2 mg/min

Carcinogenic Compounds

Substance	Carcinogenicity
Acetaldehyde CH ₃ CHO	Animal Carcinogen
Acrylamide CH ₂ =CHCONH ₂	Suspected Human Carcinogen
Acrylonitrile CH ₂ =CHCN	Suspected Human Carcinogen
Aldrin C ₁₂ H ₈ Cl ₆	Suspected Human Carcinogen
Allyl Chloride CH ₂ =CHCH ₂ Cl	Suspected Human Carcinogen
4-Aminodiphenyl	Confirmed Human Carcinogen
Amitrole	Suspected Human Carcinogen
Aniline and homologues C ₆ H ₅ NH ₂	Suspected Human Carcinogen
Anisidine (o & p) isomers NH ₂ C ₆ H ₄ OCH ₃	Suspected Human Carcinogen
Antimony compounds - as Sb Sb	Suspected Human Carcinogen
Arsenic and compounds except Arsine (as As) As	Confirmed Human Carcinogen
Arsine AsH ₃	Suspected Human Carcinogen
Asbestos - all forms	Confirmed Human Carcinogen
Asphalt - petroleum fumes	Suspected Human Carcinogen
Benz(a)anthracene	Suspected Human Carcinogen
Benzene C ₆ H ₆	Confirmed Human Carcinogen
Benzidine	Confirmed Human Carcinogen
Benzo(b)fluoranthene	Suspected Human Carcinogen
Benzo(a)pyrene	Suspected Human Carcinogen
Benzyl acetate	Animal Carcinogen
Benzyl Chloride C ₆ H ₅ CH ₂ Cl	Suspected Human Carcinogen
Beryllium and compounds - as Be Be	Suspected Human Carcinogen

1,3-Butadiene (Buta-1,3-diene) CH ₂ =CHCH=CH ₂	Suspected Human Carcinogen
tert-Butyl Chromate - as CrO ₃	Suspected Human Carcinogen
Cadmium compounds Cd	Suspected Human Carcinogen
Calcium Chromate	Suspected Human Carcinogen
Captafol (ISO) C ₁₀ H ₉ Cl ₄ NO ₂ S	Suspected Human Carcinogen
Captan (ISO) C ₉ H ₈ Cl ₃ NO ₂ S	Suspected Human Carcinogen
Carbon Black C	Suspected Human Carcinogen
Carbon Tetrachloride CCl ₄	Animal Carcinogen
Chlordane (ISO) C ₁₀ H ₆ Cl ₈	Suspected Human Carcinogen
Chlorinated Camphene (Toxaphene)	Suspected Human Carcinogen
Chlorodiphenyl (42% Chlorine)	Suspected Human Carcinogen
Chlorodiphenyl (54% Chlorine)	Suspected Human Carcinogen
Chloroform CHCl ₃	Suspected Human Carcinogen
bis(Chloromethyl) ether	Confirmed Human Carcinogen
Chloromethyl methyl ether	Suspected Human Carcinogen
beta-Chloroprene CH ₂ =CClCH=CH ₂	Suspected Human Carcinogen
Chromite Ore processing - as Cr	Confirmed Human Carcinogen
Chromium IV compounds	Confirmed Human Carcinogen
Chromyl Chloride	Suspected Human Carcinogen
Chrysene	Suspected Human Carcinogen
Coal Tar pitch volatiles - as cyclohexane solubles	Confirmed Human Carcinogen
Cobalt metal - dust and fumes Co	Animal Carcinogen
Crotonaldehyde CH ₃ CH=CHCHO	Suspected Human Carcinogen
DDT (Dichlorodiphenyltrichloroethane) C ₁₄ H ₉ Cl ₅	Suspected Human Carcinogen
Diazomethane CH ₂ N ₂	Suspected Human Carcinogen
Dichloroacetylene ClCCCl	Suspected Human Carcinogen

p-Dichlorobenzene C ₆ H ₄ Cl ₂	Animal Carcinogen
3,3'-Dichlorobenzidine	Suspected Human Carcinogen
1,4-Dichloro-2-butene	Suspected Human Carcinogen
Dichloroethyl ether	Suspected Human Carcinogen
1,3-Dichloropropene CHClCHCH ₂ Cl	Suspected Human Carcinogen
Dieldrin (ISO) C ₁₂ H ₆ Cl ₆ O	Suspected Human Carcinogen
Diglycidyl ether (DGE) (OCH ₂ CHCH ₂) ₂ O	Suspected Human Carcinogen
Dimethyl carbamoyl chloride	Suspected Human Carcinogen
1,1-Dimethyl hydrazine	Suspected Human Carcinogen
Dimethyl sulphate (CH ₃) ₂ SO ₄	Suspected Human Carcinogen
Dinitrotoluene CH ₃ C ₆ H ₃ (NO ₂) ₂	Suspected Human Carcinogen
Dioxane OCH ₂ CH ₂ OCH ₂ CH ₂	Suspected Human Carcinogen
Di-sec-octyl phthalate	Suspected Human Carcinogen
Epichlorohydrin OCH ₂ CHCH ₂ Cl	Suspected Human Carcinogen
Ethyl acrylate CH ₂ =CHCOOC ₂ H ₅	Suspected Human Carcinogen
Ethyl bromide C ₂ H ₅ Br	Suspected Human Carcinogen
Ethylene dibromide BrCH ₂ CH ₂ Br	Suspected Human Carcinogen
Ethylene dichloride ClCH ₂ CH ₂ Cl	Suspected Human Carcinogen
Ethylene imine CH ₂ CH ₂ NH	Suspected Human Carcinogen
Ethylene oxide	Suspected Human Carcinogen
Formaldehyde	Suspected Human Carcinogen
Gasoline	Suspected Human Carcinogen
Heptachlor and heptachlor epoxide C ₁₀ H ₅ Cl ₇	Suspected Human Carcinogen
Hexachlorobenzene - Skin	Suspected Human Carcinogen
Hexachlorobutadiene	Suspected Human Carcinogen
Hexachloroethane CCl ₃ CCl ₃	Suspected Human Carcinogen

Hexamethyl phosphoramidate	Suspected Human Carcinogen
Hydrazine NH ₂ NH ₂	Suspected Human Carcinogen
Lead - inorganic dusts and fumes - as Pb	Suspected Human Carcinogen
Lead Chromate	Suspected Human Carcinogen
Lindane C ₆ H ₅ Cl ₆	Suspected Human Carcinogen
Methoxychlor (ISO) C ₁₆ H ₁₅ Cl ₃ O ₂	Suspected Human Carcinogen
Methyl bromide - Skin CH ₃ Br	Suspected Human Carcinogen
Methyl chloride CH ₃ Cl	Suspected Human Carcinogen
Methylene chloride (Dichloromethane) CH ₂ Cl ₂	Suspected Human Carcinogen
4,4'-Methylene bis(2-chloroaniline) (MOCA)	Suspected Human Carcinogen
4,4'-Methylene dianiline H ₂ NC ₆ H ₄ CH ₂ C ₆ H ₄ NH ₂	Suspected Human Carcinogen
Methyl hydrazine	Suspected Human Carcinogen
Methyl iodide CH ₃ I	Suspected Human Carcinogen
beta-Naphthylamine	Confirmed Human Carcinogen
Nickel metal and insoluble compounds	Confirmed Human Carcinogen
Nickel, soluble compounds as Ni	Confirmed Human Carcinogen
p-Nitrochlorobenzene	Suspected Human Carcinogen
4-Nitrodiphenyl	Confirmed Human Carcinogen
2-Nitropropane CH ₃ CH(NO ₂)CH ₃	Suspected Human Carcinogen
N-Nitrosodimethylamine	Suspected Human Carcinogen
Oil mist, mildly refined cont. benzene	Confirmed Human Carcinogen
Pentachlorophenol C ₆ Cl ₅ OH	Suspected Human Carcinogen
Perchloroethylene (Tetrachloroethylene) CCl ₂ =CCl ₂	Animal Carcinogen
N-Phenyl-beta-naphthylamine	Suspected Human Carcinogen
o-Phenylenediamine C ₆ H ₄ (NH ₂) ₂	Suspected Human Carcinogen
Phenyglycidylether (Phenyl-2,3-epoxypropylether) C ₆ H ₅ OCH ₂ CHCH ₂ O	Suspected Human Carcinogen

Phenylhydrazine C ₆ H ₅ NHNH ₂	Suspected Human Carcinogen
Propane sultone	Suspected Human Carcinogen
beta-Propiolactone	Suspected Human Carcinogen
Propylene dichloride	Suspected Human Carcinogen
Propylene imine	Suspected Human Carcinogen
Propylene oxide	Suspected Human Carcinogen
Rosin, core solder pyro products - formaldehyde	Sensitiser, reduce exposure as much as possible
Strontium chromate as Cr	Suspected Human Carcinogen
Styrene, monomer C ₆ H ₅ CHCH ₂	Suspected Human Carcinogen
1,1,2,2-Tetrachloroethane	Suspected Human Carcinogen
Tetranitromethane	Suspected Human Carcinogen
o-Tolidine	Suspected Human Carcinogen
o-Toluidine	Suspected Human Carcinogen
p-Toluidine	Suspected Human Carcinogen
1,1,2-Trichloroethane CH ₂ ClCHCl ₂	Suspected Human Carcinogen
Trichloroethylene	Not Suspected as a Human Carcinogen
1,2,3-Trichloropropane CH ₂ ClCHClCH ₂ Cl	Suspected Human Carcinogen
2,4,6-Trinitrotoluene (TNT) CH ₃ C ₆ H ₂ (NO ₂) ₃	Suspected Human Carcinogen
Uranium, all compounds - as U	Suspected Human Carcinogen
Vinyl acetate CH ₃ COOCHCH ₂	Animal Carcinogen
Vinyl bromide CH ₂ CHBr	Suspected Human Carcinogen
Vinyl chloride	Confirmed Human Carcinogen
4-Vinyl cyclohexene	Suspected Human Carcinogen
Vinyl cyclohexene dioxide C ₆ H ₁₀ O ₂	Suspected Human Carcinogen
Vinylidene chloride	Suspected Human Carcinogen
Welding fumes	Suspected Human Carcinogen

Wood dust (certain hardwoods)	Suspected Human Carcinogen
Soft wood dusts	Suspected Human Carcinogen
Xylidene, mixed isomers (CH ₃) ₂ C ₆ H ₃ NH ₂	Suspected Human Carcinogen
Zinc chromates	Confirmed Human Carcinogen

Occupational Exposure Limits - Control Limits

Substance	TWA OEL-RL ppm	TWA OEL-RL mg/m ³	Short Term OEL-RL ppm	Short Term OEL-RL mg/m ³	1995 Notes
Acrylamide CH ₂ =CHCONH ₂	-	0.3	-	-	Sk
Acrylonitrile CH ₂ =CHCN	2	4			Sk
Arsenic and compounds As	-	0.1	-	-	except Arsine (as As)
Asbestos - all forms					See Asbestos Regulations
Benzene C ₆ H ₆	5	16			
Bis-(chloromethyl) ether (BCME) ClCH ₂ OCH ₂ Cl	0.001	0.005			New
Buta-1,3-diene CH ₂ =CHCH=CH ₂	10	22			
2-Butoxyethanol (EGBE) C ₄ H ₉ OCH ₂ CH ₂ OH	25	120			Sk
Cadmium compounds except CdO fumes and CdS Cd	-	0.05	-	-	
Cadmium Oxide fumes CdO		0.05		0.05	
Cadmium Sulphide pigments (respirable dust Cd) CdS		0.04			
Carbon Disulphide CS ₂	10	30			Sk
Chromium IV compounds		0.05			

1,2 Dibromoethane (ethylene dibromide) BrCH ₂ CH ₂ Br	0.5	4			Sk
Dichloromethane CH ₂ Cl ₂	100	350			
2,2'Dichloro-4,4'methylene dianiline (MbOCA) CH ₃ (C ₆ H ₃ Cl ₂ NH ₂) ₂		0.005			Sk
2-Ethoxyethanol C ₂ H ₅ OCH ₂ CH ₂ OH	10	37			Sk
2-Ethoxyethyl acetate C ₂ H ₅ OCH ₂ CH ₂ OOCCH ₃	10	54			Sk
Ethylene oxide	5	10			
Formaldehyde	2	2.5	2	2.5	
Grain dust See Annexure 7		10			Sen
Hydrogen cyanide			10	10	Sk
Isocyanate (all isomers) as NCO		0.02		0.07	Sen
Lead and compounds- as Pb					See the Lead Regulations
2-Methoxyethanol CH ₃ OCH ₂ CH ₂ OH	5	16			Sk
2-Methoxyethyl acetate CH ₃ COOCH ₂ CH ₂ OCH ₃	5	24			Sk
Nickel Ni		0.05			
Nickel compounds as Ni		0.1	0.5		soluble insoluble
Rubber process dust		8			See Annexure 6
Rubber fume		0.6			
Silica crystalline SiO ₂		0.4			respirable dust
Styrene C ₆ H ₅ CH=CH ₂	100	420	250	1050	
1,1,1-Trichloroethane CH ₃ CCl ₃	350	1900	450	2450	
Trichloroethylene CCl ₂ =CHCl	100	535	150	802	Skin
Vinyl chloride CH ₂ =CHCl	7				annual TWA OEL- CL of 3 ppm
Vinylidene chloride CH ₂ =CCl ₂	10	40			
Wood dust (hard wood)		5			Sen

Occupational Exposure Limits - Recommended Limits

Substance	TWA OEL-RL ppm	TWA OEL-RL mg/m ³	Short Term OEL-RL ppm	Short Term OEL-RL mg/m ³	1995 Notes
Acetaldehyde CH ₃ CHO	100	180	150	270	
Acetic acid CH ₃ COOH	10	25	15	37	
Acetic anhydride (CH ₃ CO) ₂ O	-	-	5	20	
Acetone CH ₃ COCH ₃	750	1780	1500	3560	
Acetonitrile CH ₃ CN	40	70	60	105	
o-Acetyl Salicylic Acid (Aspirin) CH ₃ COOC ₆ H ₄ COOH	-	5	-	-	
Acrolein (Acrylaldehyde) CH ₂ =CHCHO	0.1	0.25	0.3	0.8	
Acrylic acid CH ₂ =CHCOOH	10	30	20	60	
Aldrin (ISO) C ₁₂ H ₈ Cl ₆	-	0.25	-	0.75	Sk
Allyl Alcohol CH ₂ =CHCH ₂ OH	2	5	4	10	Sk
Allyl Chloride CH ₂ =CHCH ₂ Cl	1	3	2	6	
1-Allyl-2,3-epoxypropyl ether CH ₂ =CHCH ₂ OCH ₂ CHCH ₂ O	5	22	10	44	Sk
Allyl glycidyl ether (AGE) CH ₂ CHCH ₂ OCH ₂ CHCH ₂ O	5	22	10	44	Sk
Aluminium - Alkyls	-	2	-	-	
Aluminium - Metal Dust	-	10, 5	-	-	[total inhalable dust] {respirable dust}
Aluminium Oxides Al ₂ O ₃ , Al(OH) ₃ , AlOOH	-	10, 5	-	-	[total inhalable dust] {respirable dust}
Aluminium - Soluble salts	-	2	-	-	
Aminodimethylbenzene (CH ₃) ₂ C ₆ H ₃ NH ₂	2	10	10	50	Sk
2-Aminoethanol NH ₂ CH ₂ CH ₂ OH	3	8	6	15	
2-Aminopyridine NH ₂ C ₅ H ₄ N	0.5	2	2	8	
Ammonia NH ₃	25	17	35	24	
Ammonium Chloride - Fumes NH ₄ Cl	-	10	-	20	
Ammonium Sulphamidate NH ₂ SO ₃ NH ₄	-	10	-	20	
n-Amyl Acetate CH ₃ COOC ₅ H ₁₁	100	530	150	800	
sec-Amyl Acetate	-	-	150	800	

CH ₃ COOCH(CH ₃)C ₃ H ₇					
Aniline and homologues C ₆ H ₅ NH ₂	2	10	5	20	Sk
Anisidine (o & p) isomers NH ₂ C ₆ H ₄ OCH ₃	0.1	0.5	-	-	Sk
Antimony compounds - as Sb - Sb	-	0.5	-	-	
Arsine AsH ₃	0.05	0.2	-	-	
Asphalt - petroleum fumes	-	5	-	10	
Asprin	-	5	-	10	
CH ₃ COOC ₆ H ₄ COOH					
Atrazine (ISO) C ₈ H ₄ CIN ₅	-	10	-	-	
Azinphos-methyl (ISO) (CH ₃ O) ₂ PSSCH ₂ (C ₇ H ₄ N ₃ O)	-	0.2	0.6	-	Sk
Azincine	0.5	1	-	-	Sk
Aziridine CH ₂ CH ₂ NH	-	10	-	-	

Substance	TWA OEL-RL ppm	TWA OEL-RL mg/m ³	Short Term OEL- RL ppm	Short Term OEL-RL mg/m ³	1995 Notes
y-BHC (ISO) C ₆ H ₅ Cl ₆	-	0.5	-	1.5	Sk
Barium soluble compounds as Ba Ba	-	0.5	-	-	
Barium Sulphate (respirable dust) - BaSO ₄	-	2	-	-	
Benomyl (ISO) C ₁₄ H ₁₈ N ₄ O ₃	-	10	-	15	
Benzenethiol C ₆ H ₅ SH	0.5	2	-	-	
Benzene-1,2,4-tricarboxylic acid 1,2 anhydride C ₉ H ₄ O ₅	-	0.04	-	-	Sen
p-Benzoquinone C ₆ H ₄ O ₂	0.1	0.4	0.3	1.2	
Benzoyl Peroxide (C ₆ H ₅ CO) ₂ O ₂	-	5	-	-	
Benzyl butyl phthalate C ₆ H ₅ CH ₂ COOC ₆ H ₄ COOC ₄ H ₉	-	5	-	-	
Benzyl Chloride C ₆ H ₅ CH ₂ Cl	1	5	-	-	
Beryllium and compounds - as Be - Be	-	0.002	-	-	
Biphenyl (C ₆ H ₅) ₂	0.2	1.5	0.6	4	
Bis (2,3-epoxypropyl) ether (OCH ₂ CHCH ₂) ₂ O	0.1	0.6	-	-	
Bis-(2-ethylhexyl) phthalate C ₆ H ₄ (COOCH ₂ CH(C ₂ H ₅)C ₄ H ₉) ₂	-	5	-	10	
2,2 Bis (p-methoxyphenyl)-1,1,1- trichloroethane C ₁₆ H ₁₅ Cl ₃ O ₂	-	10	-	-	
Bismuth Telluride (Di-Bismuth Tri- Telluride) Bi ₂ Te ₃	-	5	-	10	

Bismuth Telluride - Se doped Bi ₂ Te ₃	-	-	-	10	
Bornan-2-one C ₁₀ H ₁₆ O	2	12	3	18	
Borates, tetra, Sodium salts Na ₂ B ₄ O ₇ (.10H ₂ O) (.5H ₂ O)	-	1, 5, 1	-	-	anhydrous, decahydrate, pentahydrate
Boron Oxide (Diboron Trioxide) B ₂ O ₃	-	10	-	20	
Boron Tribromide BBr ₃	-	-	1	10	
Boron Trifluoride BF ₃	-	-	1	3	
Bromacil (ISO) C ₉ H ₁₃ BrN ₂ O ₂	1	10	2	20	
Bromine Br ₂	0.1	0.7	0.3	2	
Bromine Pentafluoride BrF ₅	0.1	0.7	0.3	2	
Bromochloromethane CH ₂ BrCl	200	1050	250	1300	
Bromoethane C ₂ H ₅ Br	200	890	250	1110	
Bromoethylene CH ₂ =CHBr	5	20	-	-	
Bromoform CHBr ₃	0.5	5	-	-	Sk
Bromomethane CH ₃ Br	5	20	15	60	Sk
Bromotrifluoromethane CF ₃ Br	1000	6100	1200	7300	
Butane C ₄ H ₁₀	600	1430	750	1780	
Butan-1-ol C ₄ H ₉ OH	-	-	50	150	Sk
Butan-2-ol C ₃ H ₆ OHCH ₃	100	300	150	450	
Butan-2-one CH ₃ COC ₂ H ₅	200	590	300	885	
trans But-2-enal CH ₃ CH=CHCHO	2	6	6	18	
n-Butyl Acetate CH ₃ COO(CH ₂) ₃ CH ₃	150	710	200	950	
sec-Butyl Acetate CH ₃ COOCH(CH ₃)CH ₂ CH ₃	200	950	250	1190	
tert-Butyl Acetate CH ₃ COOC(CH ₃) ₃	200	950	250	1190	
n-Butyl Acrylate C ₇ H ₁₂ O ₂	10	55	-	-	
n-Butyl Alcohol C ₄ H ₉ OH	-	-	50	150	Sk
sec-Butyl Alcohol CH ₃ CH ₂ CHOHCH ₃	100	300	150	450	
tert-Butyl Alcohol (CH ₃) ₃ COH	100	300	150	450	
n-Butylamine C ₄ H ₉ NH ₂	-	-	5	15	Sk
Butyl benzyl phthalate C ₆ H ₅ CH ₂ COOC ₆ H ₄ COOC ₄ H ₉	-	5	-	-	
n-Butyl chloroformate ClCO ₂ C ₄ H ₉	1	5.6	-	-	
n-Butyl Glycidyl Ether (BGE) C ₄ H ₉ OCH ₂ CHCH ₂ O	25	135	-	-	
Butyl-2,3-epoxypropyl ether C ₄ H ₉ OCH ₂ CHCH ₂ O	25	135	-	-	
n-Butyl Lactate C ₇ H ₁₄ O ₃	5	25	-	-	
2-sec-Butylphenol C ₂ H ₅ (CH ₃)CHC ₆ H ₄ OH	5	30	-	-	Sk

Substance	TWA OEL- RL ppm	TWA OEL- RL mg/m ³	Short Term OEL-RL ppm	Short Term OEL-RL mg/m ³	1995 Notes
Caesium hydroxide CsOH	-	2	-	-	
Calcium Carbonate CaCO ₃	-	10, 5	-	-	total inhalable dust, respirable dust
Calcium Cyanamide CaNCN	-	0.5	-	1	
Calcium Hydroxide Ca(OH) ₂	-	5	-	-	
Calcium Oxide CaO	-	2	-	-	
Calcium Silicate	-	10, 5	-	-	total inhalable dust, respirable dust
Camphor - synthetic C ₁₀ H ₁₆ O	2	12	3	18	
Caprolactam dust NH(CH ₂) ₅ CO	-	1	-	3	
Caprolactam vapour NH(CH ₂) ₅ CO	5	20	10	40	
Captafol (ISO) C ₁₀ H ₉ Cl ₄ NO ₂ S	-	0.1	-	-	Sk
Captan (ISO) C ₉ H ₈ Cl ₃ NO ₂ S	-	5	-	15	
Carbaryl (ISO) C ₁₀ H ₇ OCONHCH ₃	-	5	-	10	
Carbofuran (ISO) C ₁₂ H ₁₅ NO ₃	-	0.1	-	-	
Carbon Black C	-	3.5	-	7	
Carbon Dioxide CO ₂	5000	9000	15000	27000	
Carbon Monoxide CO	50	55	300	330	
Carbon tetrabromide CBr ₄	0.1	1.4	0.3	4	
Carbon Tetrachloride CCl ₄	2	12.6	-	-	Sk
Carbonyl Chloride COCl ₂	-	0.4	-	-	Sk
Catechol C ₆ H ₄ (OH) ₂	5	20	-	-	
Cellulose	-	10, 5	-	20	total inhalable dust, respirable dust
Cement	-	10, 5	-	-	total inhalable dust, respirable dust
Chlordane (ISO)	-	0.5	-	2	Sk

C10H6Cl8					
Chlorinated biphenyls C12H7Cl3 (approx) C6H2Cl3C6H3Cl2	-	1, 0.5	-	2, 1	42% Cl, 54% Cl
Chlorine Cl2	0.5	1.5	1	3	
Chlorine Dioxide ClO2	0.1	0.3	0.3	0.9	
Chlorine Trifluoride ClF3	-	-	0.1	0.4	
Chloroacetaldehyde ClCH2CHO	-	-	1	3	
2-Chloroacetophenone C6H5COCH2Cl	0.05	0.3	-	-	
Chloroacetyl Chloride ClCH2COCl	0.05	0.2	-	-	
Chlorobenzene C6H5Cl	50	230	-	-	
Chlorobromomethane CH2BrCl	200	1050	250	1300	
2-Chloro-1,3-butadiene CH2=CClCH=CH2	10	36	-	-	Sk
Chlorodifluoromethane CHClF2	1000	3500	-	-	
1-Chloro-2,3-epoxypropane OCH2CHCH2Cl	2	8	5	20	Sk
Chloroethane C2H5Cl	1000	2600	1250	3250	
2-Chloroethanol ClCH2CH2OH	-	-	1	3	Sk
Chloroethylene CH2=CHCl	7	-	-	-	
Chloroform CHCl3	2	9.8	-	-	Sk
Chloromethane CH3Cl	50	105	100	210	
1-Chloro-4-nitrobenzene ClC6H4NO2	-	1	-	2	Sk
Chloropentafluoroethane CClF2CF3	1000	6320	-	-	
Chloropicrin CCl3NO2	0.1	0.7	0.3	2	
beta-Chloroprene CH2=CClCH=CH2	10	36	-	-	Sk
3-Chloropropene CH2=CHCH2Cl	1	3	2	6	
Chlorosulphonic acid HSO3Cl	-	1	-	-	
alpha-Chlorotoluene C6H5CH2Cl	1	5	-	-	
2-Chlorotoluene C7H7Cl	50	250	-	-	
2-Cl-6-trichloromethyl pyridine C6H3Cl4N	-	10	-	20	
Chloropyrifos (ISO)	-	0.2	-	0.6	Sk

C9H11Cl3NO3PS					
Chromium Cr	-	0.5	-	-	
Chromium II compounds - as Cr Cr	-	0.5	-	-	
Chromium III compounds - as Cr Cr	-	0.5	-	-	
Coal Dust	-	2	-	-	Respirable dust
Coal Tar pitch volatiles - as cyclohexane solubles	-	0.14	-	-	
Cobalt metal - dust and fumes Co	-	0.1	-	-	
Copper fumes Cu	-	0.2	-	-	
Copper dusts and mists - as Cu Cu	-	1	-	2	
Cotton Dust - raw	-	0.5	-	-	See Annexure 4
Cresol - all isomers	5	22	-	-	Sk
CH3C6H4OH					
Cristobalite, respirable dust SiO2					
Crotonaldehyde CH3CH=CHCHO	2	6	6	18	
Cryofluorane (INN) CCIF2CCIF2	1000	7000	1250	8750	
Cumene C6H5CH(CH3)2	25	120	75	370	Sk
Cyanamide H2NCN	-	2	-	-	
Cyanides - as CN	-	5	-	-	Sk
Cyanogen (CN)2	10	20	-	-	
Cyanogen Chloride ClCN	-	-	0.3	0.6	
Cyclohexane C6H12	100	340	300	1030	
Cyclohexanol C6H11OH	50	200	-	-	Sk
Cyclohexanone C6H10O	25	100	100	400	Sk
Cyclohexene C6H10	300	1015	-	-	
Cyclohexylamine C6H11NH2	10	40	-	-	Sk
Cyclonite (RDX) C3H6N6O6	-	1.5	-	3	Sk
Cyhexatin (ISO) (C6H11)3SnOH	-	5	-	10	

Substance	TWA OEL-RL ppm	TWA OEL-RL mg/m ³	Short Term OEL-RL ppm	Short Term OEL-RL mg/m ³	1995 Notes
2,4-D C6H3Cl2OCH2COOH	-	10	-	20	
DDM H2NC6H4CH2C6H4NH2	0.1	0.8	0.5	4	
DDT (Dichlorodiphenyltrichloroethane)	-	1	-	3	


C14H9Cl5						
DDVP (CH3O)2POOCHCl2	0.1	1	-	3		Sk
2,4 DES C8H7Cl2NaO5S	-	10	-	20		
DMDT C16H15Cl3O2	-	10	-	-		
Derris, commercial C23H22O6	-	5	-	10		
Diacetone Alcohol CH3COCH2C(CH3)2OH	50	240	75	360		
Dialkyl 7-9 phthalate C6H4(COOC7-9H15-19)2	-	5	-	-		
Dialkyl phthalate C6H4(COOCH2CHCH)2	-	5	-	-		
2,2'-Diaminodiethylamine (NH2CH2CH2)2NH	1	4	-	-		Sk
4,4'-Diaminodiphenylmethane (DADPM) H2NC6H4CH2C6H4NH2	0.1	0.8	0.5	4		
1,2-Diaminoethane NH2CH2CH2NH2	10	25	-	-		
Diammonium peroxodisulphate (as S2O8) (NH4)2S2O8	-	1	-	-		
Diatomaceous earth, respirable dust	-	1.5	-	-		
Diazinon - (ISO) C12H21N2O3PS	-	0.1	-	0.3		Sk
Diazomethane CH2N2	0.2	0.4	-	-		
Dibenzoyl peroxide (C6H5CO)2O2		5	-	-		
Diborane B2H6	0.1	0.1	-	-		
Dibrom 1,2-Dibromo-2,2- dichloroethyl dimethyl P C4H7Br2Cl2O4P	-	3	-	6		
Dibromodifluoromethane CBr2F2	100	860	150	1290		
Dibutyl Hydrogen Phosphate Di- n-butyl phosphate (n- C4H9O)2(OH)PO	1	5	2	10		
Dibutyl Phthalate C6H4(CO2C4H9)2	-	5	-	10		
6,6'-Di-tert-butyl-4,4'-thiodi-m- cresol C22H30O2S	-	10	-	20		
Dichloroacetylene ClCCCl	-	-	0.1	0.4		
1,2-Dichlorobenzene C6H4Cl2	-	-	50	300		
1,4-Dichlorobenzene C6H4Cl2	25	150	50	300		
Dichlorobenzene	75	450	-	-		
Dichloro difluoro methane CCl2F2	1000	4950	1250	6200		
1,3-Dichloro 5,5-dimethyl hydantoin C5H6Cl2N2O2	-	0.2	-	0.4		

Dichlorodiphenyltrichloroethane C ₁₄ H ₉ Cl ₅	-	1	-	3	
1,1-Dichloroethane CH ₃ CHCl ₂	200	810	400	1620	
1,2-Dichloroethane CH ₂ ClCH ₂ Cl	10	40	15	60	
1,1-Dichloroethylene CH ₂ CCl ₂	10	40	-	-	
1,2-Dichloroethylene cis:trans isomers 60:40 ClCH=CHCl	200	790	250	1000	
Dichlorofluoromethane CHCl ₂ F	10	40	-	-	
2,4-Dichlorophenoxyacetic acid C ₆ H ₃ Cl ₂ OCH ₂ COOH	-	10	-	20	
1,3-Dichloropropene cis and trans isomers CHClCHCH ₂ Cl	1	5	10	50	Sk
Dichlorotetrafluoroethane CClF ₂ CClF ₂	1000	7000	1250	8750	
Dichlorvos (ISO) (CH ₃ O) ₂ POOCH=CCl ₂	0.1	1	0.3	3	Sk
Dicyclohexyl phthalate C ₆ H ₄ (COOC ₆ H ₁₁) ₂	-	5	-	-	
Dicyclopentadiene C ₁₀ H ₁₂	5	30	-	-	
Dicyclopentadienyl iron C ₁₀ H ₁₀ Fe	-	10	-	20	
Dieldrin (ISO) C ₁₂ H ₈ Cl ₆ O	-	0.25	-	0.75	Sk
Diethanolamine HO(CH ₂) ₂ NH(CH ₂) ₂ OH	3	15	-	-	
Diethylamine (C ₂ H ₅) ₂ NH	10	30	25	75	
2-Diethylaminoethanol (C ₂ H ₅) ₂ NCH ₂ CH ₂ OH	10	50	-	-	Sk
Diethylene glycol (HOCH ₂ CH ₂) ₂ O	23	100	-	-	
Diethylamine triamine (NH ₂ CH ₂ CH ₂) ₂ NH	1	4	-	-	Sk
Diethyl ether C ₂ H ₅ OC ₂ H ₅	400	1200	500	1500	
Di-(2-ethylhexyl) phthalate (dioctyl phthalate) C ₆ H ₄ (COOCH ₂ CH(C ₂ H ₅)- C ₄ H ₉) ₂	-	5	-	10	
Diethyl ketone C ₂ H ₅ COC ₂ H ₅	200	700	250	875	
Diethyl phthalate C ₆ H ₄ (COOC ₂ H ₅) ₂	-	5	-	10	
Difluorochloromethane CHClF ₂	1000	3500	-	-	
Diglycidyl ether (DGE) (OCH ₂ CHCH ₂) ₂ O	0.1	0.6	-	-	
o-Dihydroxybenzene C ₆ H ₄ (OH) ₂	5	20	-	-	
m-Dihydroxybenzene C ₆ H ₄ (OH) ₂	10	45	20	90	

p-Dihydroxybenzene C ₆ H ₄ (OH) ₂	-	2	-	4	
1,2-Dihydroxyethane CH ₂ OHCH ₂ OH	-	10	-	60, 125	particulate, vapour
Diisobutyl ketone ((CH ₃) ₂ CHCH ₂) ₂ CO	25	150	-	-	
Diisobutyl phthalate C ₆ H ₄ (COOCH ₂ CH(CH ₃) ₂) ₂	-	5	-	-	
Diisodecyl phthalate (C ₁₀ H ₂₁ CO ₂) ₂ C ₆ H ₄	-	5	-	-	
Diisononyl phthalate C ₆ H ₄ (COOC ₉ H ₁₉) ₂	-	5	-	-	
Diisooctyl phthalate C ₆ H ₄ (CO ₂ C ₈ H ₁₇) ₂	-	5	-	-	
Diisopropylamine (CH ₃) ₂ CHNHCH(CH ₃) ₂	5	20	-	-	Sk
Diisopropyl ether (CH ₃) ₂ CHOCH(CH ₃) ₂	250	1050	310	1320	
Di-linear 79 phthalate C ₆ H ₄ (COOC ₇₋₉ H ₁₅₋₁₉) ₂	-	5	-	-	
Dimethoxymethane CH ₂ (OCH ₃) ₂	1000	3100	1250	3880	
N,N-Dimethyl acetamide CH ₃ CON(CH ₃) ₂	10	36	20	71	Sk
Dimethylamine (CH ₃) ₂ NH	10	18	-	-	
NN-Dimethylaniline C ₆ H ₅ N(CH ₃) ₂	5	25	10	50	Sk
1,3-Dimethylbutyl acetate CH ₃ CO ₂ CH(CH ₃)CH ₂ CH- (CH ₃) ₂	50	300	100	600	
NN-Dimethylethylamine C ₂ H ₅ (CH ₃) ₂ N	10	30	15	45	
Dimethylformamide HCON(CH ₃) ₂	10	30	20	60	Sk
2,6-Dimethylheptan-4-one ((CH ₃) ₂ CHCH ₂) ₂ CO	25	150	-	-	
Dimethyl phthalate C ₆ H ₄ (COOCH ₃) ₂	-	5	-	10	
Dimethyl sulphate (CH ₃) ₂ SO ₄	0.1	0.5	0.1	0.5	Sk
Dinitolmide	-	5	-	-	
Dinitrobenzene all isomers C ₆ H ₄ (NO ₂) ₂	0.15	1	0.5	3	Sk
Dinitro-o-cresol CH ₃ C ₆ H ₂ (OH)(NO ₂) ₂	-	0.2	-	0.6	Sk
2,4-Dinitrotoluene CH ₃ C ₆ H ₃ (NO ₂) ₂	-	1.5	-	5	Sk
Dinonyl phthalate C ₆ H ₄ (COOC ₉ H ₁₉) ₂	-	5	-	-	

Di-sec-octyl phthalate C ₆ H ₄ (COOCH ₂ CH(C ₂ H ₅)- C ₄ H ₉) ₂	-	5	-	10	
1,4-Dioxane, tech. grade OCH ₂ CH ₂ OCH ₂ CH ₂	25	90	100	360	Sk
Dioxathion (ISO) C ₁₂ H ₂₆ O ₆ P ₂ S ₂	-	0.2	-	-	Sk
Diphenyl (C ₆ H ₅) ₂	0.2	1.5	0.6	4	
Diphenylamine (C ₆ H ₅) ₂ NH	-	10	-	20	
Diphenyl ether (vapour) C ₆ H ₅ OC ₆ H ₅	1	7	-	-	
Diphosphorus pentasulphide P ₂ S ₅	-	1	-	3	
Dipotassium peroxodisulphate as S ₂ O ₈ K ₂ S ₂ O ₈	-	1	-	-	
Diquat dibromide (ISO) C ₁₂ H ₁₂ Br ₂ N ₂	-	0.5	-	1	
Disodium disulphite Na ₂ S ₂ O ₅	-	5	-	-	
Disodium peroxodisulphate (measured as S ₂ O ₈) Na ₂ S ₂ O ₈	-	1	-	-	
Disodium tetraborate Na ₂ B ₄ O ₇ (.10H ₂ O) (.5H ₂ O)	-	1, 5, 1	-	-	anhydrous, decahydrate, pentahydrate
Disulfoton (ISO) (C ₂ H ₅ O) ₂ PSCH ₂ CH ₂ SC ₂ H ₅	-	0.1	-	0.3	
Disulphur dichloride S ₂ Cl ₂	-		1	6	
Disulphur decafluoride S ₂ F ₁₀	0.025	0.25	0.075	0.75	
2,6-Di-tert-butyl-p-cresol (C ₄ H ₉) ₂ CH ₃ C ₆ H ₂ OH	-	10	-	-	
Diuron (ISO) C ₉ H ₁₀ Cl ₂ N ₂ O	-	10	-	-	
Divanadium pentoxide (as V) V ₂ O ₅	-	0.5, 0.05	-	-	total inhalable dust, fume & respirable dust
Divinyl benzene C ₈ H ₄ (CHCH ₂) ₂	10	50	-	-	
Dusts	-	-	-	-	see paragraph 36 of Annexure 1
Substance	TWA OEL-RL ppm	TWA OEL-RL mg/m ³	Short Term OEL- RL ppm	Short Term OEL-RL mg/m ³	1995 Notes
Emery	-	10, 5	-	-	total inhalable dust, respirable dust
Endosulfan (ISO) C ₉ H ₆ Cl ₆ O ₃ S	-	0.1	-	0.3	Sk
Endrin (ISO) C ₁₂ H ₈ Cl ₆ O	-	0.1	-	0.3	Sk

Enflurane CHFCICF2OCF2H	20	150	-		
Epichlorohydrin OCH2CHCH2Cl	2	8	5	20	Sk
1,2-Epoxy-4-epoxyethyl cyclohexane C6H12O2	10	60	-	-	
2,3-Epoxypropyl isopropyl ether C3H7OCH2CHCH2O	50	240	75	360	
Ethane-1,2-diol CH2OHCH2OH	-	10, 60	-	125	particulate, vapour
Ethanethiol C2H5SH	0.5	1	2	3	
Ethanol C2H5OH	1000	1900	-	-	
Ethanolamine NH2CH2CH2OH	3	8	500	1500	
Ether C2H5OC2H5	400	1200	-	-	
Ethyl acetate CH3COOC2H5	400	1400	-	-	
Ethyl acrylate CH2=CHCOOC2H5	5	20	15	60	Sk
Ethyl alcohol C2H5OH	1000	1900	-	-	
Ethylamine C2H5NH2	10	18	-	-	
Ethyl amyl ketone CH3CH2COCH2CH3CHCH2CH3	25	130	-	-	
Ethyl benzene C6H5C2H5	100	435	125	545	
Ethyl bromide C2H5Br	200	890	250	1110	
Ethyl butyl ketone CH3CH2CO(CH2)3CH3	50	230	75	345	
Ethyl chloride C2H5Cl	1000	2600	1250	3250	
Ethyl chloroformate ClCO2C2H5	1	4.4	-	-	
Ethylene					
Ethylene chlorohydrin ClCH2CH2OH	-	-	1	3	Sk
Ethylenediamine NH2CH2CH2NH2	10	25	-	-	
Ethylene dibromide BrCH2CH2Br	0.5	4	-	-	Sk
Ethylene dichloride CH2ClCH2Cl	10	40	15	60	
Ethylene dinitrate CH2NO3CH2NO3	0.2	1.2	0.2	1.2	Sk
Ethylene glycol CH2OHCH2OH	-	10, 60	-	125	particulate, vapour
Ethylene glycol dinitrate (EGDN) CH2NO3CH2NO3	0.2	1.2	0.2	1.2	Sk
Ethylene glycol monobutyl ether C4H9OCH2CH2OH	25	120	-	-	Sk
Ethylene glycol monoethyl ether C2H5OCH2CH2OH	10	37	-	-	Sk
Ethylene glycol monoethyl ether acetate C2H5OCH2CH2OOCCH3	10	54	-	-	Sk
Ethylene glycol monomethyl ether acetate	5	24	-	-	Sk




Ethylene glycol monomethyl ether $\text{CH}_3\text{OCH}_2\text{CH}_2\text{OH}$	5	16	-	-	Sk
Ethyleneimine $\text{CH}_2\text{CH}_2\text{NH}$	0.5	1	-	-	Sk
Ethylene oxide $\text{CH}_2\text{CH}_2\text{O}$	5	10	-	-	
Ethyl ether $\text{C}_2\text{H}_5\text{OC}_2\text{H}_5$	400	1200	500	1500	
Ethyl formate HCOOC_2H_5	100	300	150	450	
2-Ethylhexyl chloroformate $\text{CICO}_2(\text{C}_2\text{H}_5)\text{CH}_2\text{CH}(\text{CH}_2)_3\text{CH}_3$	1	7.9	-	-	
Ethylidene dichloride CH_3CHCl_2	200	810	400	1620	
Ethyl mercaptan $\text{C}_2\text{H}_5\text{SH}$	0.5	1	2	3	
4-Ethylmorpholine $\text{C}_6\text{H}_{13}\text{NO}$	5	23	20	95	Sk
Ethyl silicate $\text{Si}(\text{OC}_2\text{H}_5)_4$	10	85	30	255	

Substance	TWA OEL-RL ppm	TWA OEL-RL mg/m ³	Short Term OEL-RL ppm	Short Term OEL-RL mg/m ³	1995 Notes
Fenchlorphos (ISO) $(\text{CH}_3\text{O})_2\text{PSOC}_6\text{H}_2\text{Cl}_3$	-	10	-	-	
Ferbam (ISO) $((\text{CH}_3)_2\text{NCSS})_3\text{Fe}$	-	10	-	20	
Ferrocene $\text{C}_{10}\text{H}_{10}\text{Fe}$	-	10	-	20	
Flourides as F F	-	2.5	-	-	
Flourine F ₂	-	-	1	1.5	
Flourodichloromethane CHCl_2F	10	40	-	-	
Flourotrichloromethane CCl_3F	1000	5600	1250	7000	
Formamide HCONH_2	20	30	30	45	
Formic Acid HCOOH	5	9	-	-	
Furfural (2-Furaldehyde) $\text{C}_5\text{H}_4\text{O}_2$	2	8	10	40	Sk
Furfuryl alcohol $\text{OCH}=\text{CHCH}=\text{CCH}_2\text{OH}$	5	20	15	60	Sk

Substance	TWA OEL-RL ppm	TWA OEL-RL mg/m ³	Short Term OEL-RL ppm	Short Term OEL-RL mg/m ³	1995 Notes
Germanium tetrahydride (Germane) GeH_4	0.2	0.6	0.6	1.8	
Glutaraldehyde $\text{OCH}(\text{CH}_2)_3\text{CHO}$	-	-	0.2	0.7	
Glycerol mist $\text{CH}_2\text{OHCH}_2\text{OHCH}_2\text{OH}$	-	10	-	-	
Glycerol trinitrate	0.2	2	0.2	2	Sk

CH ₂ NO ₃ CHNO ₃ CH ₂ NO ₃					
Glycol monoethyl ether C ₂ H ₅ OCH ₂ CH ₂ OH	10	37	0.2	2	Sk
Graphite C	-	10, 5	-	-	total inhalable dust, respirable dust
Guthion (CH ₃ O) ₂ PSSCH ₂ (C ₇ H ₄ N ₃ O)	-	0.2	0.6	-	Sk
Gypsum CaSO ₄ -2H ₂ O	-	10, 5	-	-	total inhalable dust, respirable dust
Substance	TWA OEL-RL ppm	TWA OEL-RL mg/m ³	Short Term OEL-RL ppm	Short Term OEL-RL mg/m ³	1995 Notes
Halothane CHBrCl-CF ₃	10	80	-	-	
γ-HCH (ISO) C ₆ H ₅ Cl ₆	-	0.5	-	1.5	Sk
Hafnium Hf	-	0.5	-	1.5	
Halothane CHBrClCF ₃	10	80	-	-	
Heptachlor and heptachlor epoxide C ₁₀ H ₅ Cl ₇	-	0.5	-	2	Sk
n-Heptane C ₇ H ₁₆	400	1600	500	2000	
Heptan-2-one CH ₃ (CH ₂) ₄ COCH ₃	50	240	-	-	
Heptan-3-one CH ₃ CH ₂ CO(CH ₂) ₃ CH ₃	50	230	75	345	
γ-Hexachlorocyclohexane (γ-HCH) C ₆ H ₅ Cl ₆	-	0.5	-	1.5	Sk
Hexachloroethane CCl ₃ CCl ₃	5	50, 10, 5	-	-	vapour, total inhalable dust, respirable dust
Hexahydro-1,3,5-trinitro- 1,3,5-triazine C ₃ H ₆ N ₆ O ₆	-	1.5	-	3	Sk
Hexane isomers other than n-Hexane C ₆ H ₁₄	500	1800	1000	3600	
n-Hexane C ₆ H ₁₄	20	70	-	-	
1,6-Hexanolactam NH(CH ₂) ₅ CO	5	20, 1	10	40, 3	vapour, dust
Hexan-2-one C ₃ H ₉ COCH ₃	5	20	-	-	Sk
Hexone (CH ₃) ₂ CHCH ₂ COCH ₃	50	205	75	300	Sk
Hexylene glycol (CH ₃) ₂ COHCH ₂ CHOHCH ₃	25	125	25	125	
Hydrazine NH ₂ NH ₂	0.1	0.1	-	-	Sk
Hydrazoic acid (as vapour) HN ₃	-	-	0.1	-	
Hydrogen bromide HBr	-	-	3	10	

Hydrogen chloride HCl	-	-	5	7	
Hydrogen fluoride (as F) HF	-	-	3	2.5	
Hydrogen peroxide H ₂ O ₂	1	1.5	2	3	
Hydrogen selenide (as Se) H ₂ Se	0.05	0.2	-	-	
Hydrogen sulphide H ₂ S	10	14	15	21	
Hydroquinone C ₆ H ₄ (OH) ₂	-	2	-	4	
4-Hydroxy-4-methyl-pentan- 2-one CH ₃ COCH ₂ C(CH ₃) ₂ OH	50	240	75	360	
2-Hydroxypropyl acrylate CH ₂ CHCOOCH ₂ CHOHCH ₃	0.5	3	-	-	Sk
Substance	TWA OEL-RL ppm	TWA OEL-RL mg/m ³	Short Term OEL-RL ppm	Short Term OEL-RL mg/m ³	1995 Notes
2,2'-Iminodiethanol HO(CH ₂) ₂ NH(CH ₂) ₂ OH	3	15	-	-	
2,2'-Iminodi(ethylamine) (NH ₂ CH ₂ CH ₂) ₂ NH	1	4	-	-	Sk
Indene C ₉ H ₈	10	45	15	70	
Indium compounds - as In	-	0.1	-	0.3	
Iodine I ₂	-	-	0.1	1	
Iodoform CHI ₃	0.6	10	1	20	
Iodomethane CH ₃ I	5	28	10	56	Sk
Iron Oxide fumes - as Fe Fe ₂ O ₃	-	5	-	10	
Iron pentacarbonyl - as Fe Fe(CO) ₅	0.01	0.08	-	-	
Iron salts soluble - as Fe	-	1	-	2	
Isoamyl acetate CH ₃ COOCH ₂ CH ₂ CH(CH ₃) ₂	100	525	125	655	
Isoamyl alcohol (CH ₃) ₂ CHCH ₂ CH ₂ OH	100	360	125	450	
Isoamyl ethyl ketone CH ₃ COCH ₂ CH ₂ CH(CH ₃) ₂	50	240	75	360	
Isobutyl acetate CH ₃ COOCH ₂ CH(CH ₃) ₂	150	700	187	875	
Isobutyl alcohol (CH ₃) ₂ CHCH ₂ OH	50	150	75	225	
Isobutyl methyl ketone (CH ₃) ₂ CHCH ₂ COCH ₃	50	205	75	300	Sk
Isoflurane CF ₃ CHClOCHF ₂	50	380	-	-	
Isooctyl alcohol (mixed isomers) C ₈ H ₁₇ OH	50	270	-	-	
Isopentyl acetate	100	525	125	655	



Isophorone C ₉ H ₁₄ O	-	-	5	25	
Isophorone diisocyanate (IPDI)	-	0.2	-	0.7	Sen
Isopropyl acetate CH ₃ COOCH(CH ₃) ₂	-	-	200	840	
Isopropyl alcohol (CH ₃) ₂ CHOH	400	960	500	1225	Sk
Isopropyl benzene C ₆ H ₅ CH(CH ₃) ₂	25	120	75	370	
Isopropyl chloroformate ClCO ₂ CH(CH ₃) ₂	1	5	-	-	
Isopropyl ether (CH ₃) ₂ CHOCH(CH ₃) ₂	250	1050	310	1320	
Isopropyl glycidyl ether (IGE) 50 C ₃ H ₇ OCH ₂ OCHCH ₂		240	75	360	

Substance	TWA OEL- RL ppm	TWA OEL- RL mg/m ³	Short Term OEL-RL ppm	Short Term OEL-RL mg/m ³	1995 Notes
-----------	--------------------	----------------------------------	--------------------------------	-------------------------------------------	------------



0.5	0.9	1.5	3	
-----	-----	-----	---	--


Substance	TWA OEL- RL ppm	TWA OEL- RL mg/m ³	Short Term OEL-RL ppm	Short Term OEL-RL mg/m ³	1995 Notes
-----------	--------------------	----------------------------------	--------------------------------	-------------------------------------------	------------



-	10, 5	-	-	total inhalable dust, respirable dust
---	-------	---	---	---------------------------------------------




-	0.5	-	1.9	Sk
---	-----	---	-----	----



1000	1800	1250	2250	
------	------	------	------	--




-	0.025	-	-	
---	-------	---	---	--




-	-	-	1	
---	---	---	---	--

Substance	TWA OEL-RL ppm	TWA OEL-RL mg/m ³	Short Term OEL- RL ppm	Short Term OEL-RL mg/m ³	1995 Notes
-----------	----------------------	------------------------------------	---------------------------------	----------------------------------------------	------------



-	0.005	-	-	Sk
---	-------	---	---	----



0.1	0.8	0.5	4	
-----	-----	-----	---	--



-	0.02	-	0.07	Sen
---	------	---	------	-----



-	10, 5	-	-	total inhalable dust, respirable dust
---	-------	---	---	---------------------------------------------

Magnesium oxide (as Mg) MgO	-	5, 10	-	10	fume and respirable dust, respirable dust
Malathion (ISO) C ₁₀ H ₁₉ O ₆ PS ₂	-	10	-	-	Sk
Maleic anhydride C ₄ H ₂ O ₃	0.25	1	-	-	
Manganese dust and compounds Mn	-	5	-	-	
Manganese fumes Mn	-	1	-	3	
Manganese cyclopentadienyl tricarbonyl C ₅ H ₅ -Mn(CO) ₃	-	0.1	-	0.3	Sk
Manganese tetroxide Mn ₃ O ₄	-	1	-	-	
Man made mineral fibre	-	-	-	-	See Annexure 3
Marble	-	10, 5	-	-	Total inhalable dust, respirable dust
Mequinol (INN) CH ₃ OC ₆ H ₄ OH	-	5	-	-	
Mercaptoacetic acid C ₂ H ₄ O ₂ S	1	5	-	-	
Mercury - Alkyl compounds as Hg Hg	-	0.01	-	0.03	Sk
Mercury all other forms - as Hg Hg	-	0.05	-	0.15	
Mesityl oxide CH ₃ COCH=C(CH ₃) ₂	15	60	25	100	
Methacrylic acid CH ₂ =C(CH ₃)COOH	20	70	40	140	
Methacrylonitrile CH ₂ =C(CH ₃)CN	1	3	-	-	Sk
Methanethiol CH ₃ SH	0.5	1	-	-	
Methanol CH ₃ OH	200	260	250	310	Sk
Methomyl (ISO) C ₅ H ₁₀ N ₂ O ₂ S	-	2.5	-	-	Sk
Methoxychlor (ISO) C ₁₆ H ₁₅ Cl ₃ O ₂	-	10	-	-	
1-Methoxy propan-2-ol CH ₃ OCH ₂ CHOHCH ₃	100	360	300	1080	Sk
Methyl acetate CH ₃ COOCH ₃	200	610	250	760	
Methyl acrylate CH ₂ =CHCOOCH ₃	10	35	-	-	Sk
Methylal CH ₃ (OCH ₃) ₂	1000	3100	1250	3880	
Methylal alcohol CH ₃ OH	200	260	250	310	Sk
Methylamine CH ₃ NH ₂	10	12	-	-	
Methyl n-amyl ketone CH ₃ (CH ₂) ₄ COCH ₃	50	240	-	-	
N-Methyl aniline C ₆ H ₅ NHCH ₃	0.5	2	-	-	Sk
Methyl bromide - Skin CH ₃ Br	5	20	15	60	Sk
3-Methylbutan-1-ol (CH ₃) ₂ CHCH ₂ CH ₂ OH	100	360	125	450	
1-Methylbutyl acetate	-	-	150	800	

CH ₃ COOCH(CH ₃)C ₃ H ₇					
Methyl n-butyl ketone CH ₃ (CH ₂) ₃ COCH ₃	5	20	-	-	Sk
Methyl chloride CH ₃ Cl	50	105	100	210	
Methyl chloroform CH ₃ CCl ₃	350	1900	450	2450	
Methyl 2-cyanoacrylate CH ₂ =C(CN)COOCH ₃	2	8	4	16	
Methylcyclohexane C ₇ H ₁₄	400	1600	500	2000	
Methylcyclohexanol CH ₃ C ₆ H ₁₀ OH	50	235	75	350	Sk
2-Methylcyclohexanone CH ₃ CHCO(CH ₂) ₃ CH ₂	50	230	75	345	Sk
Methylcyclopentadienyl manganese tricarbonyl (as Mn)	-	0.1	-	0.6	
2-Methyl-4,6-dinitrophenol CH ₃ C ₆ H ₂ (OH)(NO ₂) ₂	-	0.2	-	0.6	Sk
4,4'-Methylene bis(2chloroaniline)- (MbOCA) CH ₂ (C ₆ H ₃ ClNH ₂) ₂	-	0.005	-	-	Sk
Methylene chloride (Dichloromethane) CH ₂ Cl ₂	100	350	250	780	
4,4'-Methylene-diphenyl diisocyanate (MDI)	-	0.02	-	0.07	Sen
4,4'-Methylenedianiline (MDA) H ₂ NC ₆ H ₄ CH ₂ C ₆ H ₄ NH ₂	0.1	0.8	0.5	4	
Methyl ethyl ketone (MEK) CH ₃ COC ₂ H ₅	200	590	300	885	
Methyl ethyl ketone peroxides C ₈ H ₁₆ O ₄ or C ₈ H ₁₈ O ₆	-	-	0.2	1.5	
Methyl formate HCOOCH ₃	100	250	150	375	
5-Methyl heptan-3-one CH ₃ CH ₂ COCH ₂ CH ₃ CH ₂ CH ₃	25	130	-	-	
5-Methyl hexan-2-one CH ₃ COCH ₂ CH ₂ CH(CH ₃) ₂	50	240	75	360	
Methyl hydrazine	0.2	0.35	0.2	0.35	Sk
Methyl iodide CH ₃ I	5	28	10	56	Sk
Methyl isoamyl ketone CH ₃ COCH ₂ CH ₂ CH(CH ₃) ₂	50	240	75	360	
Methyl isobutyl carbinol CH ₃ CHOHCH ₂ CH(CH ₃) ₂	25	100	40	160	Sk
Methyl isobutyl ketone (MIBK) (CH ₃) ₂ CHCH ₂ COCH ₃	50	205	75	300	Sk
Methyl isocyanate	-	0.02	-	0.07	Sen
Methyl mercaptan CH ₃ SH	0.5	1	-	-	
Methyl methacrylate CH ₂ =C(CH ₃)COOCH ₃	100	410	125	510	
Methyl parathion C ₈ H ₁₀ NO ₅ PS	-	0.2	-	0.6	Sk
2-Methylpentane-2,4-diol	25	125	25	125	

(CH ₃) ₂ COHCH ₂ CH) ₂ HCH ₃					
4-Methylpentan-2-ol CH ₃ CHOHCH ₂ CH(CH ₃) ₂	25	100	40	160	Sk
4-Methylpentan-2-one (CH ₃) ₂ CHCH ₂ COCH ₃	50	205	75	300	Sk
4-Methylpent-3-and-2-one CH ₃ COCH=C(CH ₃) ₂	15	60	25	100	
4-Methyl-m-phenylene diisocyanate	-	0.02	-	0.07	Sen
2-Methylpropan-1-ol (CH ₃) ₂ CHCH ₂ OH	50	150	75	225	
2-Methylpropan-2-ol (CH ₃) ₃ COH	100	300	150	450	
Methyl propyl ketone CH ₃ COC ₃ H ₇	200	700	250	875	
1-Methyl-2-pyrrolidone CH ₃ N(CH ₂) ₃ CO	100	400	-	-	
Methyl silicate (CH ₃ O) ₄ Si	1	6	5	30	
alpha Methyl styrene C ₆ H ₅ C(CH ₃)=CH ₂	-	-	100	480	
Methyl styrene (all isomers) CH ₃ C ₆ H ₄ CH=CH ₂	100	480	150	720	
n-Methyl-n,2,4,6-tetranitro aniline (NO ₂) ₃ C ₆ H ₂ N(NO ₂)CH ₃	-	1.5	-	3	Sk
Mevinphos (ISO) C ₇ H ₁₃ O ₆ P	0.01	0.1	0.03	0.3	Sk
Mica	-	10, 1	-	-	total inhalable dust, respirable dust
Molybdenum, soluble compounds - as Mo	-	5	-	10	
Molybdenum, insoluble compounds, as Mo	-	10	-	20	
Monochloroacetic acid ClCH ₂ CO ₂ H	0.3	1	-	-	Sk
Morpholine C ₄ H ₉ NO	20	70	30	105	Sk

Substance	TWA OEL- RL ppm	TWA OEL- RL mg/m ³	Short Term OEL-RL ppm	Short Term OEL-RL mg/m ³	1995 Notes
Naled (ISO) C ₄ H ₇ Br ₂ Cl ₂ O ₄ P	-	3	-	6	Sk
Naphthalene C ₁₀ H ₈	10	50	15	75	
1,5-Naphthylene diisocyanate	-	0.02	-	0.07	Sen
Nickel carbonyl Ni(CO) ₄	-	-	0.1	0.24	
Nickel, organic compounds (as Ni)	-	1	-	3	
Nicotine C ₁₀ H ₁₄ N ₂	-	0.5	-	1.5	Sk

Nitrapyrin C ₆ H ₃ Cl ₄ N	-	10	-	20	
Nitric acid HNO ₃	2	5	4	10	
Nitric oxide NO	25	30	35	45	
4-Nitroaniline NO ₂ C ₆ H ₄ NH ₂	-	6	-	-	Sk
Nitrobenzene C ₆ H ₅ NO ₂	1	5	2	10	Sk
Nitroethane C ₂ H ₅ NO ₂	100	310	-	-	
Nitrogen dioxide NO ₂	3	5	5	9	
Nitrogen monoxide NO	25	30	35	45	
Nitrogen trifluoride NF ₃	10	30	15	45	
Nitroglycerin CH ₂ NO ₂ CHNO ₃ CH ₂ NO ₃	0.2	2	0.2	2	Sk
Nitromethane CH ₃ NO ₂	100	250	150	375	
1-Nitropropane C ₃ H ₇ NO ₂	25	90	-	-	
2-Nitropropane CH ₃ CH(NO ₂)CH ₃	10	36	20	72	
Nitrotoluene (all isomers) CH ₃ C ₆ H ₄ NO ₂	5	30	10	60	Sk
Nitrous oxide N ₂ O	100	180	-	-	
Substance	TWA OEL- RL ppm	TWA OEL- RL mg/m ³	Short Term OEL-RL ppm	Short Term OEL-RL mg/m ³	1995 Notes
Octachloronaphthalene C ₁₀ Cl ₈	-	0.1	-	0.3	Sk
n-Octane CH ₃ (CH ₂) ₆ CH ₃	300	1450	375	1800	
Orthophosphoric acid H ₃ PO ₄	-	1	-	3	
Osmium tetroxide - as Os OsO ₄	0.0002	0.002	0.0006	0.006	
Oxalic acid COOHCOOH	-	1	-	2	
Oxalonitrile (CN) ₂	10	20	-	-	
2,2'-Oxydiethanol (HOCH ₂ CH ₂) ₂ O	23	100	-	-	
Ozone O ₃	0.1	0.2	0.3	0.6	
Substance	TWA OEL- RL ppm	TWA OEL- RL mg/m ³	Short Term OEL-RL ppm	Short Term OEL-RL mg/m ³	1995 Notes
PCB's	-	-	-	-	see chlorinated biphenyls
Paraffin wax fumes	-	2	-	6	
Paraquat dichloride (CH ₃ (C ₅ H ₄ N ⁺) ₂ CH ₃)-	-	0.1	-	-	Respirable dust

(Cl-2)					
Parathion (ISO) (C ₂ H ₅ O) ₂ PSOC ₆ H ₄ NO ₂	-	0.1	-	0.3	Sk
Parathion-methyl (ISO) C ₈ H ₁₀ NO ₅ PS	-	0.2	-	0.6	Sk
Pentacarbonyliron (as Fe) Fe(CO) ₅	0.01	0.08	-	-	
Pentachlorophenol C ₆ Cl ₅ OH	-	0.5	-	1.5	Sk
Pentaerythritol C(CH ₂ OH) ₄	-	10, 5	-	20	total inhalable dust, respirable dust
Pentane C ₅ H ₁₂	600	1800	750	2250	
2-Pentanone, 3- Pentanone CH ₃ COC ₂ H ₇	200	700	250	875	
Pentyl acetate CH ₃ COOC ₅ H ₁₁	100	530	150	800	
Perchloroethylene (Tetrachloroethylene) CCl ₂ =CCl ₂	50	335	150	1000	
Perchloryl flouride ClO ₃ F	3	14	6	28	
Phenacyl chloride C ₆ H ₅ COCH ₂ Cl	0.05	0.3	-	-	
Phenol C ₆ H ₅ OH	5	19	10	38	Sk
p-Phenylenediamine C ₆ H ₄ (NH ₂) ₂	-	0.1	-	-	Sk
Phenyl-2,3-epoxypropyl ether C ₆ H ₅ OCH ₂ CHCH ₂ O	1	6	-	-	
Phenylethylene C ₆ H ₅ CH=CH ₂	100	420	250	1050	
Phenylhydrazine C ₆ H ₅ NHNH ₂	5	20	10	45	Sk
2-Phenylpropene C ₆ H ₅ C(CH ₃)=CH ₂	-	-	100	480	
Phorate (ISO) C ₇ H ₁₇ O ₂ PS ₃	-	0.05	-	0.2	Sk
Phosdrin C ₇ H ₁₃ O ₆ P	0.01	0.1	0.03	0.3	Sk
Phosgene COCl ₂	0.1	0.4	-	-	
Phosphine PH ₃	-	-	0.3	0.4	
Phosphorus (yellow) P ₄	-	0.1	-	0.3	
Phosphorus pentachloride PCl ₅	0.1	1	-	-	
Phosphorus pentasulphide P ₂ S ₅	-	1	-	3	
Phosphorus trichloride PCl ₃	0.2	1.5	0.5	3	
Phosphoryl trichloride	0.2	1.2	0.6	3.6	

POCl ₃					
Phthalic anhydride C ₆ H ₄ (CO ₂)O	1	6	4	24	Sen
Picloram (ISO) C ₆ H ₃ Cl ₃ N ₂ O ₂	-	10	-	20	
Picric acid HOC ₆ H ₂ (NO ₂) ₃	-	0.1	-	0.3	Sk
Piperazine dihydrochloride C ₄ H ₁₀ N ₂ .2HCl	-	5	-	-	
Piperidine C ₅ H ₁₁ N	1	3.5	-	-	Sk
Plaster of Paris (Calcium sulphate) (CaSO ₄) ₂ H ₂ O	-	10, 5	-	-	total inhalable dust, respirable dust
Platinum metal Pt	-	5	-	-	
Platinum, soluble salts - as Pt Pt	-	0.002	-	-	Sen
Polychlorinated biphenyls -			-	-	See chlorinated biphenyls
Polyvinyl chloride (PVC) -	-	10, 5	-	-	total inhalable dust, respirable dust
Portland cement	-	10, 5	-	-	total inhalable dust, respirable dust
Potassium hydroxide KOH	-	-	-	2	
Propane-1,2-diol CH ₃ CHOHCH ₂ OH	150	470, 10	-	-	vapour + particulates, particulates
n-Propanol CH ₃ CH ₂ CH ₂ OH	200	500	250	625	Sk
Propan-1-ol CH ₃ CH ₂ CH ₂ OH	200	500	250	625	Sk
Propan-2-ol (CH ₃) ₂ CHOH	400	980	500	1225	Sk
Propargyl alcohol HCCCH ₂ OH	1	2	3	6	Sk
Propionic acid CH ₃ CH ₂ COOH	10	30	15	45	
Propoxur (ISO) H ₃ CNHCOOC ₆ H ₄ OCH- (CH ₃) ₂	-	0.5	-	2	
n-Propyl acetate CH ₃ COOC ₃ H ₇	200	840	250	1050	
Propylene dinitrate CH ₂ NO ₃ CHNO ₃ CH ₃	0.2	1.2	0.2	1.2	Sk
Propylene glycol	-	-	-	-	See Propane-

CH3CHOHCH2OH					1,2-diol above
Propylene glycol dinitrate - CH2NO3CHNO3CH3	-	-	-	-	See Propylene dinitrate above
Propylene glycol monomethyl ether CH3OCH2CHOHCH3	100	360	300	1080	Sk
Prop-2-yn-1-ol HC=CCH2OH	1	2	3	6	Sk
Pulverised Fuel Ash	-	10, 5	-	-	total inhalable dust, respirable dust
Pyrethrum (Pyrethrins) (ISO)	-	5	-	10	
Pyridine C5H5N	5	15	10	30	
2-Pyridylamine NH2C5H4N	0.5	2	2	8	
Pyrocatechol C6H4(OH)2	5	20	-	-	

Substance	TWA OEL- RL ppm	TWA OEL- RL mg/m³	Short Term OEL-RL ppm	Short Term 1995 Notes OEL-RL mg/m³	
Quartz, crystalline SiO2	-	0.4	-	-	respirable dust
Quinone C6H4O2	0.1	0.4	0.3	1.2	

Substance	TWA OEL- RL ppm	TWA OEL- RL mg/m³	Short Term OEL-RL ppm	Short Term 1995 Notes OEL-RL mg/m³	
RDX C3H6N6O8	-	1.5	-	3	Sk
Resorcinol C6H4(OH)2	10	45	20	90	
Rhodium metal and insoluble compounds - as Rh Rh	-	0.1	-	0.3	metal fumes and dust
Rhodium, soluble compounds as Rh Rh	-	0.001	-	0.003	soluble salts
Ronnel (CH3O)2PSOC6H2Cl3	-	10	-	-	
Rosin, core solder pyro products - formaldehyde	-	0.1	-	0.3	Sen
Rotenone (commercial) (ISO) C23H22O6	-	5	-	10	
Rouge	-	10, 5	-	-	total inhalable dust, respirable dust

Substance	TWA OEL- RL ppm	TWA OEL- RL mg/m³	Short Term	Short Term 1995 Notes OEL-RL
-----------	--------------------	----------------------	---------------	---------------------------------

			OEL-RL ppm	mg/m ³	
Selenium and compounds - as Se	-	0.1	-	-	
Silane SiH ₄	0.5	0.7	1	1.5	
Silica, amorphous SiO ₂	-	6, 3	-	-	total inhalable dust, respirable dust
Silica, fused SiO ₂	-	0.1	-	-	respirable dust
Silicon Si	-	10, 5	-	-	Total inhalable dust, respirable dust
Silicon carbide SiC	-	10, 5	-	-	Total inhalable dust, respirable dust
Silicon tetrahydride - Silane SiH ₄	0.5	0.7	1	1.5	
Silver metal Ag	-	0.1	-	-	
Silver, soluble compounds - as Ag	-	0.01	-	-	
Sodium azide NaN ₃	-	-	-	0.3	
Sodium 2,4-dichlorophenoxyethyl sulphate C ₈ H ₇ Cl ₂ NaO ₃ S	-	10	-	20	
Sodium fluoroacetate CH ₂ FCOONa	-	0.05	-	0.15	Sk
Sodium hydrogen sulphite NaHSO ₃	-	5	-	-	
Sodium hydroxide NaOH	-	-	-	2	
Sodium metabisulphite Na ₂ S ₂ O ₅	-	5	-	-	
Starch	-	10, 5	-	-	total inhalable dust, respirable dust
Stibine SbH ₃	0.1	0.5	0.3	1.5	
Strychnine C ₂₁ H ₂₂ N ₂ O ₃	-	0.15	-	0.45	
Styrene, monomer C ₆ H ₅ CH=CH ₂	100	420	250	1050	
Subtilisins (proteolytic enzymes)	-	0.00006	-	0.00008	
Sucrose C ₁₂ H ₂₂ O ₁₁	-	10	-	20	
Sulfotep (ISO) (C ₂ H ₅) ₄ P ₂ S ₂ O ₅	-	0.2	-	-	Sk
Sulphur dioxide SO ₂	2	5	5	15	
Sulphur hexafluoride SF ₆	1000	6000	1250	7500	
Sulphuric acid H ₂ SO ₄	-	1	-	-	
Sulphur monochloride S ₂ Cl ₂	-	-	1	6	

Sulphur pentachloride S2F10	0.025	0.25	0.075	0.75
Sulphur tetrafluoride SF4	0.1	0.4	0.3	1
Sulphuryl fluoride (Sulphuryl difluoride) SO2F2	5	20	10	40

Substance	TWA OEL- RL ppm	TWA OEL- RL mg/m ³	Short Term OEL-RL ppm	Short Term OEL- RL mg/m ³	1995 Notes
2,4,5-T (ISO) C8H5Cl3O3	-	10	-	20	
TDI	-	0.02	-	0.07	Sen
TEDP (Tetraethyl dithiopyrophosphate) (C2H5)4P2S2O5	-	0.2	-	-	Sk
TEPP (ISO) (Tetraethyl pyrophosphate) (C2H5)4P2O7	0.004	0.05	0.01	0.2	Sk
Talc (containing no asbestos fibers)	-	10, 1	-	-	total inhalable dust, respirable dust
Tantalum metal and oxide dusts - as Ta Ta	-	5	-	10	
Tellurium and compounds - as Te Te	-	0.1	-	-	except Hydrogen Telluride
Terphenyls, all isomers C18H14	-	-	0.5	5	
1,1,2,2-Tetrabromoethane CHBr2CHBr2	0.5	7	-	-	Sk
Tetrabromomethane CBr4	0.1	1.4	0.3	4	
Tetracarbonylnickel (as Ni) Ni(CO)4	-	-	0.1	0.24	
1,1,1,2-Tetrachloro-2,2- difluoroethane CCl3CClF2	100	834	100	834	
1,1,2,2-Tetrachloro-1,2- difluoroethane CCl2FCCl2F	100	834	100	834	
Tetrachloroethene CCl2CCl2	50	335	150	1000	
Tetrachloromethane CCl4	2	12.6	-	-	Sk
Tetrachloronaphthalene, all isomers C10H4Cl4	-	2	-	4	
O,O,O',O'-Tetraethyl dithiopyrophosphate (C2H5)4P2S2O5	-	0.2	-	-	Sk
O,O,O',O'-Tetraethyl pyrophosphate	0.004	0.05	0.01	0.2	Sk

(C ₂ H ₅) ₄ P ₂ O ₇					
Tetraethyl orthosilicate Si(OC ₂ H ₅) ₄	10	85	30	255	
Tetraflourochloroethane CClF ₂ CClF ₂	1000	7000	1250	8750	
Tetrahydrofuran (C ₂ H ₄) ₂ O	200	590	250	735	
Tetramethyl orthosilicate (CH ₃ O) ₄ Si	1	6	5	30	
Tetramethyl succinonitrile C ₈ H ₁₂ N ₂	0.5	3	2	9	Sk
Tetrasodium pyrophosphate Na ₄ P ₂ O ₇	-	5	-	-	Sk
Tetryl (NO ₂) ₃ C ₆ H ₂ N(NO ₂)CH ₃	-	1.5	-	3	Sk
Thallium, soluble compounds Tl	-	0.1	-	-	Sk
4,4'-Thio bis(6-tert butyl- m-cresol) C ₂₂ H ₃₀ O ₂ S	-	10	-	20	
Thioglycolic acid C ₂ H ₄ O ₂ S	1	5	-	-	
Thionyl chloride SOCl ₂	-	-	1	5	
Thiram (ISO) (CH ₃) ₂ NCS ₂ CS ₂ N(CH ₃) ₂	-	5	-	10	
Tin, oxide and inorganics except SnH ₄ Sn	-	2	-	4	
Tin, organic compounds as Sn except Cyhexatin Sn	-	0.1	-	0.2	Sk
Titanium dioxide TiO ₂	-	10, 5	-	-	total inhalable dust, respirable dust
Toluene C ₆ H ₅ CH ₃	50	188	150	560	Sk
Toluene, 2,4 diisocyanate (TDI)	-	0.02	-	0.07	Sen
p-Toluenesulphonyl chloride CH ₃ C ₆ H ₄ SO ₂ Cl	-	-	-	5	
1,4,7-Tri-(aza)-heptane (NH ₂ CH ₂ CH ₂) ₂ OH	1	4	-	-	Sk
Tribromomethane CHBr ₃	0.5	5	-	-	Sk
Tributyl phosphate, all isomers (C ₄ H ₉) ₃ PO ₄	-	5	-	5	
Tricarbonyl (eta- cyclopentadienyl) manganese (as Mn) (C ₅ H ₅)-Mn(CO) ₃	-	0.1	-	0.3	Sk
Tricarbonyl (methylcyclopentadienyl)	-	0.2	-	0.6	Sk

manganese (as Mn) (CH ₃) ₅ H ₄ -Mn(CO) ₃					
Trichloroacetic acid CCl ₃ COOH	1	5	-	-	
1,2,4-Trichlorobenzene C ₆ H ₃ Cl ₃	5	40	5	40	
1,1,1-Trichlorobis (chlorophenyl) ethane C ₁₄ H ₉ Cl ₅	-	1	-	3	
1,1,2-Trichloroethane CH ₂ ClCHCl ₂	10	45	20	90	Sk
Trichlorofluoromethane CClF ₃	1000	5600	1250	7000	
Trichloromethane CHCl ₃	2	9.8	-	-	
Trichloronitromethane CCl ₃ NO ₂	0.1	0.7	0.3	2	
2,4,5-Trichlorophenoxy acetic acid C ₈ H ₅ Cl ₃ O ₃	-	10	-	20	
1,2,3-Trichloropropane CH ₂ ClCHClCH ₂ Cl	50	300	75	450	Sk
1,1,2-Trichloro-1,2,2- trifluoroethane CCl ₂ FC ₂ F ₂	1000	7600	1250	9500	
Tri-o-Cresyl phosphate (CH ₃ C ₆ H ₄ O) ₃ PO	-	0.1	-	0.3	
Tricyclohexyl tin hydroxide - (C ₆ H ₁₁) ₃ SnOH	-	5	-	10	
Tridymite SiO ₂	-	0.4	-	-	respirable dust
Triethylamine (C ₂ H ₅) ₃ N	10	40	15	60	
Trifluorobromomethane CF ₃ Br	1000	6100	1200	7300	
Trimanganese tetraoxide Mn ₃ O ₄	-	1	-	-	
Trimellitic anhydride C ₉ H ₄ O ₅	-	0.04	-	-	Sen
Trimethylamine (CH ₃) ₃ N	10	24	15	36	
Trimethylbenzene all isomers and mixtures C ₆ H ₃ (CH ₃) ₃	25	123	-		
3,5,5-Trimethylcyclohex-2- enone C ₉ H ₁₄ O	-	-	5	25	
Trimethyl phosphite (CH ₃ O) ₃ P	2	10	-	-	
2,4,6-Trinitrophenol HOC ₆ H ₂ (NO ₂) ₃	-	0.1	-	0.3	Sk
2,4,6-Trinitrotoluene (TNT) CH ₃ C ₆ H ₂ (NO ₂) ₃	-	0.5	-	-	Sk
Triphenyl phosphate	-	3	-	6	

(C6H5)3PO4

Tripoli, respirable dust SiO2	-	0.4	-	-
Tri-o-tolyl phosphate (CH3C6H4O)3PO	-	0.1	-	0.3
Tungsten, insoluble compounds - as W W	-	5	-	10
Tungsten, soluble compounds - as W W	-	1	-	3
Turpentine C10H16	100	560	150	840

Substance	TWA OEL- RL ppm	TWA OEL- RL mg/m ³	Short Term OEL-RL ppm	Short Term 1995 Notes OEL-RL mg/m ³
Uranium, all compounds -- as U U	-	0.2	-	0.6

Substance	TWA OEL- RL ppm	TWA OEL- RL mg/m ³	Short Term OEL-RL ppm	Short Term 1995 Notes OEL-RL mg/m ³
Vanadium pentoxide V2O5	-	0.5, 0.05	-	- total inhale, fume and respirable dust
Vinyl acetate CH3COOCHCH2	10	30	20	60
Vinyl benzene C6H5CH=CH2	100	420	250	1050
Vinyl bromide CH2CHBr	5	20	-	-
Vinyl chloride	5	15	-	-
4-Vinyl cyclohexene	0.1	0.4	-	-
Vinyl cyclohexene dioxide C6H12O2	10	60	-	-
Vinyl toluene C6H5C(CH3)CH2	-	-	100	480

Substance	TWA OEL- RL ppm	TWA OEL- RL mg/m ³	Short Term OEL-RL ppm	Short Term 1995 Notes OEL-RL mg/m ³
Warfarin (ISO) C19H16O4	-	0.1	-	0.3
White spirit	100	575	125	720

Substance	TWA OEL- RL ppm	TWA OEL- RL mg/m ³	Short Term OEL-RL	Short Term 1995 Notes OEL-RL mg/m ³
-----------	--------------------	----------------------------------	-------------------------	------------------------------------------------------

Xylene, all and mixed isomers C ₆ H ₄ (CH ₃) ₂	100	435	150	650	Sk
Xylidene, mixed isomers (CH ₃) ₂ C ₆ H ₃ NH ₂	2	10	10	50	Sk
Substance	TWA OEL- RL ppm	TWA OEL- RL mg/m ³	Short Term OEL-RL ppm	Short Term OEL-RL mg/m ³	1995 Notes
Yttrium, as metal and compounds Y	-	1	-	3	
Substance	TWA OEL- RL ppm	TWA OEL- RL mg/m ³	Short Term OEL-RL ppm	Short Term OEL-RL mg/m ³	1995 Notes
Zinc chloride fumes ZnCl ₂	-	1	-	2	
Zinc di-stearate Zn(C ₁₈ H ₃₅ O ₂) ₂	-	10, 5	-	20	total inhalable dust, respirable dust
Zinc oxide fumes ZnO	-	5	-	10	
Zirconium and compounds - as Zr Zr	-	5	-	10	

Annexure 2 - Calculation of exposure with regard to the specified reference periods

This Annexure reproduces the approved method for the calculation of exposure in relation to the 8-hour, short-term and one-year reference periods.

1. THE 8-HOUR REFERENCE PERIOD

1.1. The term '8-hour reference period' relates to the procedure whereby the occupational exposures in any 24-hour period are treated as equivalent to a single uniform exposure for 8 hours [the 8-hour time weighted average (TWA) exposure].

1.2. The 8-hour TWA may be represented mathematically by:

$$\frac{C_1T_1 + C_2T_2 + \dots + C_nT_n}{8}$$

where C(1) is the occupational exposure value (concentration) and T(1) is the associated exposure time in hours in any 24-hour period.

Examples

a. The operator works for 7h20 min. on a process in which he is exposed to a substance hazardous to health. The average exposure during that period is measured as 0.12 mg/m³. The 8 - hour TWA therefore is - 7h20min (7.33h) at 0.12mg/m³

$$\begin{aligned} & 40 \text{ min (0.67h) at } 0 \text{ mg/m}^3 \\ \text{That is - } & \frac{(0.12 \times 7.33) + (0 \times 0.67)}{8} \\ & = 0.11 \text{ mg/m}^3 \end{aligned}$$

b. The operator works for eight hours on a process in which he is exposed to a substance hazardous to health. The average exposure during that period is measured as 0,15mg/m³. The 8-hour TWA therefore is -

$$\frac{0.15 \times 8}{8}$$

$$= 0.15 \text{ mg/m}^3$$

c. Working periods may be split into several sessions for the purpose of sampling to take account of rest and meal breaks, etc. This is illustrated by the following example:

Working period	Exposure {mg/m ³ }	Duration of sampling (h)
08:00 - 10:30	0.32	2.5
10:45 - 12:45	0.07	2
13:30 - 1 5:30	0.20	2
15:45 - 17:15	0.10	1.5

Exposure is assumed to be zero during the period 10:30 to 10:45, 12:45 to 13:30 and 15:30 to 15:45.

The 8-hour TWA therefore is -

$$\frac{(0.32 \times 2.5) + (0.07 \times 2) + (0.20 \times 2) + (0.10 \times 1.5) + (0 \times 1.25)}{8}$$

$$= 0.19 \text{ mg/m}^3$$

d. An operator works for eight hours during the night shift on a process in which he is intermittently exposed to a substance hazardous to health. The operators work pattern during the working period should be known and the best available data relating to each period of exposure should be applied in calculating the 8-hour TWA. This data should be based on direct measurement, estimates based on data already available or reasonable assumptions.

Working period	Task	Exposure (mg/m ³)
22:00 - 24:00	Helping in workshop	1. 10 (known to be the exposure of full-time group in the workshop)
24:00 - 01:00	Cleaning elsewhere in factory	0 (assumed)
1.00 - 04:00	Working in canteen	0 (assumed)
04:00 - 06:00	Cleaning up after breakdown in workshop	0.21 (assumed)

The 8-hour TWA therefore is -

$$\frac{(0.10 \times 2) + (0.21 \times 2) + (0 \times 4)}{8}$$

$$= 0.78 \text{ mg/m}^3$$

2. THE SHORT-TERM REFERENCE PERIOD

Exposure should be recorded as the average over the specified short-term reference period and should normally be determined by sampling over that period.

Example where the short-term reference period is 15 minutes.

a. Exposure period is less than 15 minutes

The sampling result should be averaged over 15 minutes. For example, if a 5-minute sample produces a level of 600 ppm and is immediately followed by a period of zero exposure, then the 15-minute average exposure will be 200 ppm:

b. Exposure period is 15 minutes or longer

Measurements should be taken over a 15-minute period and the result is the 15-minute average exposure. Measurements for periods greater than 15 minutes should not be used to calculate a 15-minute average exposure, but if the average exposure over the longer period exceeds the 15-minute exposure limit, then this limit must have been exceeded over some 15-minute period.

3. THE ONE-YEAR REFERENCE PERIOD FOR VINYL CHLORIDE

Exposure should be recorded as the time-weighted average of vinyl chloride in the atmosphere of a work-ing area over a period of one year. At enclosed vinyl chloride polymerisation plants, continuous or permanent sequential sampling methods must be used. Where discontinuous measurements are made, the frequency of measurements and the number per year should be such that it is possible to state with a statistical confidence coefficient of at least 95% that the true

mean annual concentration did not exceed the annual maximum exposure limit. Only periods of plant operation including, where necessary, maintenance time should be taken into account.

Annexure 3 - Methods of measurement and calculation for determining fibre concentrations of manmade mineral fibre

1. The method must determine the exposure of employees by sampling in the breathing zone of the employee exposed.
2. 'Fibre' means a particle with a length $> 5 \mu\text{m}$, an average diameter $< 3 \mu\text{m}$, and a ratio of length to diameter > 3 to 1, which can be seen using the system specified in paragraph 3.
3. Fibres shall be counted in accordance with AIA RTM1.
4. The results shall be regularly tested by quality assurance procedures to ensure that the results are in satisfactory agreement with the average of results, obtained by approved inspection authorities (AIA) participating in a national quality assurance scheme, using the method specified in paragraphs 1 to 3 above.

Annexure 4 - Cotton Dust

1. The OEL for cotton dust is 0.5 mg/m³ total dust less fly, 8-hour TWA. This figure is not a personal exposure limit but a background air standard determined by using static samplers. This OEL-RL applies to dust from the processing and handling of raw and waste cotton, including blends containing raw or waste cotton, with the following exceptions:
 - a. dust from weaving, knitting, braiding and subsequent processes; and
 - b. dust from bleached or dyed cotton.
2. Under the HCS Regulations, assessors must satisfy themselves that the assessment takes account of people who work intensively with the material e.g. at bale opening, waste handling, maintenance of dust extraction equipment and cleaning procedures, and who are therefore likely to be exposed to dust.
3. Where the OEL-RL does not apply, exposure should be kept below both 10 mg/m³ 8-hour TWA total inhalable dust and 5 mg/m³ 8-hour TWA respirable dust, determined by a personal sampling method.

Annexure 5 - Asphyxiants

1. Some gases and vapours, when present at high concentration in air, act as simple asphyxiants by reducing the oxygen content by dilution to such an extent that life cannot be supported. Many asphyxiants are odourless, colourless and not readily detectable. Monitoring the oxygen content of the air is often the best means of ensuring safety. The oxygen content of air in the workplace should never be allowed to fall below a minimum of 18% by volume under normal atmospheric pressure. Particular care is necessary when dense asphyxiants, e.g. argon, are used, since very high localised concentrations can arise owing to their collecting in pits, confined spaces and other low-lying areas where ventilation is likely to be poor.
2. Many asphyxiants present a fire or explosion risk. The concentration at which these risks can arise are liable to be well below those levels at which asphyxiation is likely to occur and should be taken into account when assessing the hazards.
3. Although asphyxiants are listed in Table 2 of Annexure 1, they are not substances hazardous to health for the purpose of the HCS Regulations.

Annexure 6 - Rubber fume and rubber process dust

1. Rubber fume is fume evolved in the mixing, milling and blending of natural rubber or synthetic elastomers, or of natural rubber and synthetic polymers combined with chemicals, and in the processes which convert the resultant blends into finished products or parts thereof, and including any inspection procedures where fume continues to be evolved.
2. The limit relates to cyclohexane soluble material determined by the method described in 'Rubber fume in air, measured as total particulates and cyclohexane soluble material'.
3. Rubber process dust is evolved during the manufacture of intermediates or articles from natural rubber and/or synthetic elastomers. This definition does not include dusts, which, for occupational purposes, can be dealt with individually. In each case the relevant OEL will apply. Otherwise, where a substance with an OEL is present in a mixed dust, the OEL for that substance will apply, in addition to the rubber process dust limit.
4. Methods for personal sampling and measurement of total inhalable dusts are available in 'General method for the gravimetric determination of respirable and total inhalable dust' and 'Rubber fume in air measures as total particulates and cyclohexane soluble material'.

Annexure 7 - The definition of Grain Dust

1. Grain dust is taken to be dust arising from the harvesting, drying, handling, storage or processing of barley, wheat, oats, maize and rye, including contaminants.

Annexure 8 : Material safety data sheet

MATERIAL SAFETY DATA SHEET	No: Date issued: Page of
COMPANY DETAILS	
Name:	Emergency telephone no.:
Address:	Telex:
Tel:	Fax:
1) Product and Company Identification: (Page 1 may be used as an emergency safety data sheet)	
Trade name :	Chemical abstract no. :
Chemical family :	NIOSH no.:
Chemical name:	Hazchem code:
Synonyms:	UN no.:
2) Composition	
Hazardous components:	
EEC classification:	
R Phrases:	

3) Hazards Identification
Main hazard:
Flammability:
Chemical hazard
Biological hazard:
Reproductive hazard:
Eye effects: eyes:
Health effects - skin:
Health effects - ingestion:
Health effects - inhalation:
Carcinogenicity:
Mutagenicity:
Neurotoxicity:
4) First-aid Measures
Product in eye:
Product on skin:
Product ingested:
Product inhaled:
5) Fire-fighting Measures
Extinguishing media:
Special hazards:
Protective clothing:
6) Accidental Release Measures
Personal precautions:
Environmental precautions:
Small spills:
Large spills:
7) Handling and Storage
Suitable material:
Handling/storage precautions:
8) Exposure Control/Personal Protection
Occupational exposure limits:

Engineering control measures:

Personal protection - respiratory:

Personal protection - hand:

Personal protection - eye:

Personal protection - skin:

Other protection:

9) Physical and Chemical Properties

Appearance:

Odour:

pH:

Boiling point:

Melting point:

Flash point:

Flammability:

Auto flammability:

Explosive properties:

Oxidizing properties:

Vapour pressure:

Density:

Solubility - water:

Solubility - solvent:

Solubility - coefficient

10) Stability and Reactivity

Conditions to avoid:

Incompatible materials:

Hazardous decomposition products:

11) Toxicological Information

Acute toxicity:

Skin and eye contact:

Chronic toxicity:

Carcinogenicity:

Mutagenicity:

Neurotoxicity:

Reproductive hazards:

12) Ecological Information

Aquatic toxicity - fish:

Aquatic toxicity - daphnia

Aquatic toxicity - algae

Biodegradability:

Bio-accumulation:

Mobility:

German wgk:

13) Disposal Considerations

Disposal methods:

Disposal of packaging:

14) Transport Information

UN no.

Substance identity no.

ADR/RID class:

ADR/RID item no.

ADR/RID hazard identity no.:

IMDG - shipping name:

MDG - class:

IMDG - packaging group:

IMDG - marine pollutant:

IMDG - EMS no.

IMDG - WAG tabel no.:

IATA - shipping name:

IATA - class:

IATA - subsidiary risk(s):

ADNR - class:

UK - description:

UK - emergency action class:

UK - classification:

Tremcard no.:

15) Regulatory Information.

EEC hazard classification:

Risk phases:

Safety phases:

National legislation:

16) Other Information